

Home	About Company	Products	Download	Certification	Distributors	Application Stories	Partners	Training	FAQ	Activity	News & Events	Catalog
------	---------------	----------	----------	---------------	--------------	---------------------	----------	----------	-----	----------	---------------	---------



Model: I-7522A



Model: I-7522AD

I-7522A/ I-7522AD

Embedded communication controller with one RS-485, one RS-422 and one RS-232



Manual

PIN
Assignment

Software



Certification



FAQ

Introduction

There are many RS-232 devices in industry applications. Nowadays it becomes important to link all those RS-232 devices together for automation & information. Usually those RS-232 devices are far away from the host-PC & widely distributed in the factory. So it is not a good idea to use multi-serial cards to connect all these RS-232 devices together. Our I-752N series products can be used to link multiple RS-232 devices by single RS-485 network. The RS-485 is famous for its easy maintenance, simple cabling, stable, reliable and low cost.

Onboard 1Kb Queue buffer

The I-752N modules are equipped with a 1Kb queue buffer for its local RS-232 device. All input data can be stored in the queue buffer until the Host PC has time to read it. These features allow the Host PC to be linked to thousands of RS-232 devices without any loss of data.

3000V isolation on RS-485 side

COM2 of the I-752N modules is an isolated RS-485 port with 3000V isolation, which will protect the local RS-232 devices from transient noises coming from the RS-485 network.

Self-Tuner ASIC inside

The interned I-752N Self-Tuner ASIC for the RS-485 port can auto detect and control the send/receive direction of the RS-485 network, meaning that there is no need for application programs to be concerned about direction control of the RS-485 network. The advanced technology which makes this possible is covered.

Can be used as Addressable RS-485 to RS-232 Converter

Most RS-232 devices don't support device addressing. The ICPDAS I-752N series assigns a unique address to any RS-232 device installed on an RS-485 network. When the Host PC sends a command with a device address to the RS-485 network, the destination I-752N module will remove the address field, and then pass the other commands to its local RS-232 devices. The response from the local RS-232 devices will be returned to the Host PC via the I-752N.

Master-type Addressable RS-485 to RS-232 Converter

ICPDAS I-752N products are unique. In that they are Master-type converters which use our R.O.C. Patent 086674, while most other converters are Slave-type, which are helpless without a Host PC. In real industrial applications, many users are not satisfied with Slave-type converters as they cannot be adapted to individual requirement. The powerful I-752N series analyzes the local RS-232 devices, DI and DO without the need for a Host PC. Refer to Applications 5~9 for more information in the manual.

Can be used as RS-485 to RS-232 Device Server

The Device Server is an appliance that network enables any device with a serial communication port. Our Intelligent Communication Controllers allow those devices to become connected to the RS-485 network. If the user wants to use Ethernet work, he can choose I-7188EN series products.

[back](#)

Features

- Built-in "Addressable RS-485 to RS-232 Converter" firmware
- Support about 30 well-defined commands
- Support Dual-Watchdog commands
- Support Power-up value & safe value for DO
- The firmware can real-time monitor the onboard DI and control the onboard DO according to user's requirement
- The firmware can real-time monitor the RS-232 device and control the onboard D/O according to user's requirement
- Watchdog timer provides fault tolerance and recovery
- Low power consumption
- R.O.C. Invention Patent No. 086674, No.103060, No. 132457

[back](#)

Specifications

Timer

Build-in Watchdog Timer Yes

Connector

For I-7521/I-7522/I-7523 Male DB-9

For I-7521/I-7522/I-7523 13-pin screw terminal block (accepts 16~26 AWG wires); 3.81mm pitch

For I-7522A/I-7524/I-7527 14-pin screw terminal block (accepts 16~22 AWG wires); 3.5mm pitch

Isolation

COM2 (self-tuner ASIC inside) Isolation voltage 3000V for I-7521/I-7522/I-7523

Self-tuner ASIC inside

For RS-485 COM2 , COM1

Communication speed

All ports 115.2K bps max

Digital Input/Output

Digital Input Input type : non-isolated
On voltage level : +1V max (Connect to GND)
Off voltage level : +3.5V~30V (Open)

Digital Output Output type : Open-collector
Output current : 100mA
Max load voltage : +30V/DC

Dimensions

I-7521/I-7522/I-7523 119mm x 72mm x 33mm

I-7522A/I-7524/I-7527 123mm x 72mm x 33mm

Operating Environment

Operating Temperature -25°C to +75°C

Storage Temperature -40°C to +80°C

Humidity 0 to 90%

Power

Protection Power reverse polarity protection

Power requirement 10 to 30V/DC

Power consumption 2W (without display)

3W (with display)

[back](#)

Applications

Factory Automation

Building Automation

Home Automation

[back](#)

Ordering information

I-7522A Embedded communication controller with one RS-485, one RS-422 and one RS-232

I-7522AD I-7522A with seven segment display

I-7522A CR Embedded communication controller with one RS-485, one RS-422 and one RS-232 (RoHS)

I-7522AD CR I-7522A with seven segment display (RoHS)

[back](#)**Accessories**[PWR-24/110](#)

Wall-plug power Adapter / 110VAC, 60Hz, 4.8W

[PWR-24/220F](#)

Wall-plug power Adapter / 220VAC, 50Hz, 2.4W

[KA-52F](#)

Wide range power Adapter / 100-250 VAC, 50-60Hz, 25W

[DIN-KA52F](#)

KA-52F with DIN-RAIL Mounting Adapter

[back](#)

Copyright© ICP DAS Co., Ltd. All Rights Reserved

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.