

<a href="#">Home</a>	<a href="#">About Company</a>	<a href="#">Products</a>	<a href="#">Download</a>	<a href="#">Certification</a>	<a href="#">Application Stories</a>	<a href="#">FAQ</a>	<a href="#">News &amp; Events</a>
				<a href="#">Distributors</a>	<a href="#">Partners</a>	<a href="#">Training</a>	<a href="#">Activity</a>
							<a href="#">Catalog</a>



Model: I-7527



Model: I-7527D

## I-7527 / I-7527D

Embedded communication controller with one RS-485 and seven RS-232



Manual

PIN  
Assignment

Software



Certification



FAQ

### Introduction

There are many RS-232 devices in industry applications. Nowadays it becomes important to link all those RS-232 devices together for automation & information. Usually those RS-232 devices are far away from the host-PC & widely distributed in the factory. So it is not a good idea to use multi-serial cards to connect all these RS-232 devices together. Our I-752N series products can be used to link multiple RS-232 devices by single RS-485 network. The RS-485 is famous for its easy maintenance, simple cabling, stable, reliable and low cost.

#### Onboard 1Kb Queue buffer

The I-752N modules are equipped with a 1Kb queue buffer for its local RS-232 device. All input data can be stored in the queue buffer until the Host PC has time to read it. These features allow the Host PC to be linked to thousands of RS-232 devices without any loss of data.

#### 3000V isolation on RS-485 side

COM2 of the I-752N modules is an isolated RS-485 port with 3000V isolation, which will protect the local RS-232 devices from transient noises coming from the RS-485 network.

#### Self-Tuner ASIC inside

The interned I-752N Self-Tuner ASIC for the RS-485 port can auto detect and control the send/receive direction of the RS-485 network, meaning that there is no need for application programs to be concerned about direction control of the RS-485 network. The advanced technology which makes this possible is covered.

#### Can be used as Addressable RS-485 to RS-232 Converter

Most RS-232 devices don't support device addressing. The ICPDAS I-752N series assigns a unique address to any RS-232 device installed on an RS-485 network. When the Host PC sends a command with a device address to the RS-485 network, the destination I-752N module will remove the address field, and then pass the other commands to its local RS-232 devices. The response from the local RS-232 devices will be returned to the Host PC via the I-752N.

#### Master-type Addressable RS-485 to RS-232 Converter

ICPDAS I-752N products are unique. In that they are Master-type converters which use our R.O.C. Patent086674, while most other converters are Slave-type, which are helpless without a Host PC. In real industrial applications, many users are not satisfied with Slave-type converters as they cannot be adapted to individual requirement.

The powerful I-752N series analyzes the local RS-232 devices, DI and DO without the need for a Host PC. Refer to

Applications 5~9 for more information in the manual.

#### Can be used as RS-485 to RS-232 Device Server

The Device Server is an appliance that network enables any device with a serial communication port. Our Intelligent Communication Controllers allow those devices to become connected to the RS-485 network. If the user wants to use Ethernet work, he can choose I-7188EN series products.

[back](#)

## Features

- Built-in "Addressable RS-485 to RS-232 Converter" firmware
- Support about 30 well-defined commands
- Support Dual-Watchdog commands
- Support Power-up value & safe value for DO
- The firmware can real-time monitor the onboard DI and control the onboard DO according to user's requirement
- The firmware can real-time monitor the RS-232 device and control the onboard D/O according to user's requirement
- Watchdog timer provides fault tolerance and recovery
- Low power consumption
- R.O.C. Invention Patent No. 086674, No.103060, No. 132457

[back](#)

## Specifications

### Timer

Build-in Watchdog Timer      Yes

### Connector

For I-7521/I-7522/I-7523      Male DB-9

For I-7521/I-7522/I-7523      13-pin screw terminal block ( accepts 16~26 AWG wires ); 3.81mm pitch

For I-7522A/I-7524/I-7527      14-pin screw terminal block ( accepts 16~22 AWG wires ); 3.5mm pitch

### Isolation

COM2 (self-tuner ASIC inside)      Isolation voltage 3000V for I-7521/I-7522/I-7523

### Self-tuner ASIC inside

For RS-485      COM2 , COM1

### Communication speed

All ports      115.2K bps max

### Digital Input/Output

Digital Input      Input type : non-isolated  
On voltage level : +1V max (Connect to GND)  
Off voltage level : +3.5V~30V (Open)

Digital Output      Output type : Open-collector  
Output current : 100mA  
Max load voltage : +30V/DC

### Dimensions

I-7521/I-7522/I-7523      119mm x 72mm x 33mm

I-7522A/I-7524/I-7527      123mm x 72mm x 33mm

### Operating Environment

Operating Temperature      -25°C to +75°C

Storage Temperature      -40°C to +80°C

Humidity      0 to 90%

### Power

Protection      Power reverse polarity protection

Power requirement      10 to 30V/DC

Power consumption      2W (without display)

3W (with display)

[back](#)

## Applications

Factory Automation

Building Automation

Home Automation

[back](#)

## Ordering information

I-7527      Embedded communication controller with one RS-485 and seven RS-232

I-7527D      I-7527 + LED display

I-7527 CR      Embedded communication controller with one RS-485 and seven RS-232 (RoHS)

I-7527D CR      I-7527 + LED display (RoHS)

[back](#)**Accessories**[PWR-24/110](#)

Wall-plug power Adapter / 110VAC, 60Hz, 4.8W

[PWR-24/220F](#)

Wall-plug power Adapter / 220VAC, 50Hz, 2.4W

[KA-52F](#)

Wide range power Adapter / 100-250 VAC, 50-60Hz, 25W

[DIN-KA52F](#)

KA-52F with DIN-RAIL Mounting Adaper

[back](#)

Copyright© ICP DAS Co., Ltd. All Rights Reserved

# Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



## AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 [obchod@autocont-ipc.cz](mailto:obchod@autocont-ipc.cz)

 +420 552 301 002

 [www.autocont-ipc.cz](http://www.autocont-ipc.cz)



### PRŮMYSLOVÉ POČÍTAČE

*fanless embedded PC, do racku, ...*



### POČÍTAČE S DISPLEJEM

*panelové PC, terminály, do vozidel, ...*



### AUTOMATIZACE A SBĚR DAT

*převodníky, karty, moduly, switche, ...*



### PERIFERIE A KOMPONENTY

*monitory, klávesnice, desky, skříně, ...*



### NOTEBOOKY A TABLETY

*odolné, windows, android, IP65, ...*



### INFORMAČNÍ KIOSKY

*interiérové, venkovní, ...*



### MEDICÍNSKÁ TECHNIKA

*počítače, tablety, LCD, klávesnice, ...*



### SOFTWAREVÁ ŘEŠENÍ

*pro výrobu, zaměstnance, kiosky, ...*



### PŘEJÍT DO E-SHOPU

[eshop.autocont-ipc.cz](http://eshop.autocont-ipc.cz)



### DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



### PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



### ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



### SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.