


CB-134I Series

4-port RS-422/485 PC/104-Plus modules with 2 KV isolation



- > 921.6 Kbps maximum baudrate for super fast data transmission
- > On-chip S/W flow control
- > Built-in 15 KV ESD protection
- > Serial interface is DIP switch selectable
- > Onboard Tx and Rx LED indicators for each port
- > Windows XP/Vista/7, Windows CE 5.0/6.0, and Windows XP embedded operating systems supported
- > Wide temperature model available for -40 to 85°C environments



: Overview

The CB-134I PC/104-Plus modules come with 4 RS-422/485 ports, and can be used with PC/104-Plus CPU boards that accept the PC/104-Plus expansion interface. Optional DB9 and DB25 connection cables are available for connecting to serial devices, and the CB-134Is'

versatile driver support makes the modules suitable for a wide range of applications. The CB-134I modules can be used on the PC/104-Plus (PCI) bus, and provide a reliable, high performance solution for multiport serial communication.

: Specifications

Hardware

Comm. Controller: MU860 (16C550C compatible)
Bus: PC/104-Plus bus
Connector: 40-pin box header
DIP Switches: Serial interface

Serial Interface

Number of Ports: 4
Serial Standards: RS-422/485
Max. No. of Boards per PC: 4

Serial Line Protection

ESD Protection: 15 KV on the board
Optical Isolation: 2 KV

Performance

Baudrate: 50 bps to 921.6 Kbps

Serial Communication Parameters

Data Bits: 5, 6, 7, 8
Stop Bits: 1, 1.5, 2
Parity: None, Even, Odd, Space, Mark
I/O Address: Assigned by BIOS
IRQ: Assigned by BIOS
FIFO: 128 bytes

Serial Signals

RS-422: TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-4w: TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-2w: Data+(B), Data-(A), GND

Driver Support

Operating Systems: Windows 9X/ME/NT/2000, Windows XP/2003/Vista/2008/7 x86/x64, Windows CE 5.0/6.0, Windows XP Embedded, DOS, Linux 2.4, Linux 2.6 x86/x64, QNX 6
Note: Please refer to Moxa's website for the latest driver support information.

Physical Characteristics

Dimensions: 90 x 96 mm (3.54 x 3.78 in)

Environmental Limits

Operating Temperature:
 Standard Models: 0 to 55°C (32 to 131°F)
 Wide Temp. Models: -40 to 85°C (-40 to 185°F)
Storage Temperature: -40 to 85°C (-40 to 185°F)
Ambient Relative Humidity: 5 to 95% (non-condensing)

Standards and Certifications

EMC: CE, FCC
EMI: EN 55022, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A
EMS: EN 55024, IEC 61000-6-2, IEC 61000-6-4, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11 (DIPS)
Green Product: RoHS, CRoHS, WEEE

MTBF (mean time between failures)

Time: 534,809 hrs
Database: Telcordia (Bellcore), GB

Power Requirements

Power Consumption: 236 mA @ 5 VDC

Warranty

Warranty Period: 5 years
Details: See www.moxa.com/warranty

: Ordering Information

Available Models

CB-134I: 4-port RS-422/485 PC/104-Plus module with optical isolation protection, 0 to 55°C operating temperature
CB-134I-T: 4-port RS-422/485 PC/104-Plus module with optical isolation protection, -40 to 85°C operating temperature

Connection Options (can be purchased separately)

CBL-F40M9x4-50: 40-pin box header to DB9 male x 4 connection cable, 50 cm
CBL-F40M25x4-50: 40-pin box header to DB25 male x 4 connection cable, 50 cm

Package Checklist

- 1 CB-134I or CB-134I-T module
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.