

ICF-1150 Series

Industrial serial-to-fiber converters



- > 3-way communication: RS-232, fiber, and RS-422/485
- > Rotary switch to change the pull high/low resistor value
- > Extend RS-232/422/485 transmission up to:
 - 40 km with single-mode
 - 5 km with multi-mode
- > 3-way Galvanic Isolation (for "I" model only)
- > -40 to 85°C wide temperature models available
- > Class I, Div. II certification



Three-Way Communication

The ICF-1150 series support 2 serial ports, with a D-sub9 connector for RS-232 communication and a removable terminal block for RS-422 or RS-485 communication. The 3 ports (2 serial ports and one fiber port) are completely independent. When an ICF-1150 converter receives data from any one port, it will send the data out through the other 2 ports. For example, once the ICF-1150 converter receives

a command from the remote master through the fiber port, it will convert the signal and send the command through the RS-232 and RS-422/485 ports at the same time. If the user is monitoring a system running on an RS-485 network, there is no need to use an additional RS-232 to RS-485 converter to connect the laptop computer's serial port to the RS-485 bus.

Rotary Switch for Setting the Pull High/Low Resistor

The RS-485 interface supports multi-drop or daisy-chain connections, which system engineers will use to connect serial devices such as meters, RTUs, and readers together on the same bus. Since the number of serial devices on the same bus will cause the impedance

of the data line to increase, the ICF-1150 allows users to tune the pull high/low resistor. Just rotate the switch to the appropriate value without removing the ICF-1150 from the DIN-rail.

Pull High/Low Resistor Values

Position	0	1	2	3	4	5	6	7	8	9
ohms	150K	10K	4.7K	3.3K	1K	909	822	770	500	485

Specifications

Optical Fiber Side

Fiber Connector: SC or ST

Cable Requirements:

Single-mode: 8.3/125, 8.7/125, 9/125, or 10/125 μm

Multi-mode: 50/125, 62.5/125, or 100/140 μm

Transmission Distance:

Single-mode: 40 km

Multi-mode: 5 km

Wavelength:

ICF-1150-S (single-mode): 1310 nm

ICF-1150-M (multi-mode): 850 nm

Tx Output:

ICF-1150-S (single-mode): > -5 dBm

ICF-1150-M (multi-mode): > -5 dBm

Rx Sensitivity:

ICF-1150-S (single-mode): -25 dBm

ICF-1150-M (multi-mode): -20 dBm

Point-to-Point Transmission: Half-duplex or full-duplex

Ring Transmission: Half-duplex

RS-232/422/485 Side

RS-232 Signals: TxD, RxD, GND

RS-422 Signals: TxD+, TxD-, RxD+, RxD-, GND

RS-485-4w Signals: TxD+, TxD-, RxD+, RxD-, GND

RS-485-2w Signals: Data+, Data-, GND

Baudrate: 50 bps to 921.6 Kbps

ESD Protection: 15 KV for all signals

Isolation: 2 KV RMS isolation per I/O port for 1 minute

Physical Characteristics

Housing: Aluminum (1 mm)
Dimensions: 30.3 x 70 x 115 mm (1.19 x 2.76 x 4.53 in)
Weight: 330 g

Environmental Limits

Operating Temperature:
 Standard Models: 0 to 60°C (32 to 140°F)
 Wide Temp. Models: -40 to 85°C (-40 to 185°F)
Storage Temperature: -40 to 85°C (-40 to 185°F)
Ambient Relative Humidity: 5 to 95% (non-condensing)

Power Requirements


Input Voltage: 12 to 48 VDC
Power Consumption:
 ICF-1150: 127 mA @ 12 V
 ICF-1150I: 163 mA @ 12 V
Voltage Reversal Protection: Protects against V+/V- reversal
Over Current Protection: 1.1 A (protects against two signals shorted together)

Standards and Certifications

Safety: UL 508
Hazardous Location: UL/cUL Class I Division 2 Groups A/B/C/D, ATEX Zone 2 EEx nC IIC
EMC: CE, FCC
EMI: EN 55022 Class B, FCC Part 15 Subpart B Class B
EMS:
 EN 61000-4-2 (ESD) Level 4,
 EN 61000-4-3 (RS) Level 2,
 EN 61000-4-4 (EFT) Level 4,
 EN 61000-4-5 (Surge) Level 3,
 EN 61000-4-6 (CS) Level 2,
 EN 61000-4-8 (PFMF) Level 3
Freefall: IEC 60068-2-32
Green Product: RoHS, CRoHS, WEEE
MTBF (mean time between failures):
Time: 792,085 hrs
Database: Telcordia (Bellcore), GB
Water and Dust Proof: IP30
Warranty
Warranty Period: 5 years
Details: See www.moxa.com/warranty


Dimensions

Unit: mm (inch)




Pin Assignment

DB9 female connector



Pin	RS-232
1	-
2	TxD
3	RxD
4	-
5	GND
6	-
7	-
8	-

Terminal block connector



Pin	RS-422/485-4w	RS-485-2w
1	GND	GND
2	RxD-(A)	Data-(A)
3	RxD+(B)	Data+(B)
4	TxD-(A)	-
5	TxD+(B)	-

: Ordering Information

Available Models

ICF-1150-M-SC: Industrial RS-232/422/485 to multimode fiber converter, SC connector, 0 to 60°C operating temperature

ICF-1150-M-ST: Industrial RS-232/422/485 to multimode fiber converter, ST connector, 0 to 60°C operating temperature

ICF-1150-S-SC: Industrial RS-232/422/485 to single mode fiber converter, SC connector, 0 to 60°C operating temperature

ICF-1150-S-ST: Industrial RS-232/422/485 to single mode fiber converter, ST connector, 0 to 60°C operating temperature

ICF-1150I-M-SC: Industrial RS-232/422/485 to multimode fiber converter, SC connector, 2 KV isolation, 0 to 60°C operating temperature

ICF-1150I-M-ST: Industrial RS-232/422/485 to multimode fiber converter, ST connector, 2 KV isolation, 0 to 60°C operating temperature

ICF-1150I-S-SC: Industrial RS-232/422/485 to single mode fiber converter, SC connector, 2 KV isolation, 0 to 60°C operating temperature

ICF-1150I-S-ST: Industrial RS-232/422/485 to single mode fiber converter, ST connector, 2 KV isolation, 0 to 60°C operating temperature

ICF-1150-M-SC-T: Industrial RS-232/422/485 to multimode fiber converter, SC connector, -40 to 85°C operating temperature

ICF-1150-M-ST-T: Industrial RS-232/422/485 to multimode fiber converter, ST connector, -40 to 85°C operating temperature

ICF-1150-S-SC-T: Industrial RS-232/422/485 to single mode fiber converter, SC connector, -40 to 85°C operating temperature

ICF-1150-S-ST-T: Industrial RS-232/422/485 to single mode fiber converter, ST connector, -40 to 85°C operating temperature

ICF-1150I-M-SC-T: Industrial RS-232/422/485 to multimode fiber converter, SC connector, 2 KV isolation, -40 to 85°C operating temperature

ICF-1150I-M-ST-T: Industrial RS-232/422/485 to multimode fiber converter, ST connector, 2 KV isolation, -40 to 85°C operating temperature

ICF-1150I-S-SC-T: Industrial RS-232/422/485 to single mode fiber converter, SC connector, 2 KV isolation, -40 to 85°C operating temperature

ICF-1150I-S-ST-T: Industrial RS-232/422/485 to single mode fiber converter, ST connector, 2 KV isolation, -40 to 85°C operating temperature

Optional Accessories

DR-4524: 45 W, 2 A Din-Rail 24 VDC power supply with universal 85 to 264 VAC input

Package Checklist

- 1 ICF-1150 series fiber converter
- Quick installation guide (printed)
- Warranty card

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.