


AIMB-223

Mobile AMD G-series Dual Core Mini-ITX
with CRT/LVDS/HDMI, 6 COM and Dual LAN



susIAccess



CE FCC

Features

- Supports AMD Mobile G-series Dual Core processor
- One 204-pin SO-DIMM up to 4 GB DDR31066/1333 MHz SDRAM
- Supports Dual display with CRT/HDMI/LVDS (eDP)
- Dual LANs, 6COM, Mini PCIe, and CFast
- Supports SUSIAccess and Embedded Software APIs

Software APIs:



SMBus



H/W Monitor



Watchdog



GPIO



Brightness

Utilities:



BIOS flash




Monitoring

Specifications

Processor System	CPU	AMD Dual Core T56N
	Max. Speed	1.65 GHz (dual core 18W TDP)
	L2 Cache	512 KB
	Chipset	AMD G-Series + A55E
	BIOS	AMI EFI 32 Mbit SPI
Expansion Slot	PCI	1
	Mini-PCIe	1
	PCIe	PCIe x1 (PCIe gen2)
Memory	Technology	One channel DDR3 1066/1333 MHz
	Max. Capacity	4 GB
	Socket	1 x 204-pin SO-DIMM (Non-ECC)
Graphics	Controller	ATI Radeon HD 6310, support DirectX 11, UVD3
	VRAM	Shared system memory up to 224 MB SDRAM
	CRT	Supports up to 2560 x 1536 @ 32bpp
	LVDS	Supports dual channel 48 bit up to 1920 x 1200
	HDMI	1920 x 1200 @ 60 MHz
Ethernet	Dual Display	CRT+LVDS, LVDS+HDMI, CRT+HDMI
	Interface	10/100/1000 Mbps
	Controller	GbE LAN1: RTL8111G-CG; GbE LAN2: RTL8111G-CG
SATA	Connector	RJ-45 x 2
	Max Data Transfer Rate	600 MB/s (SATA 3.0)
EIDE	Channel	4
	Mode	None
SSD	Channel	None
	CFast CompactFlash	CFast type I/II
Rear I/O	CRT	1
	HDMI	1
	Ethernet	2
	USB	4 (USB 2.0 compliant)
	Audio	3 (Mic-in, Line-out, Line-in)
	Serial	2 (RS-232)
	DCjack	1 (2.5 mm)
Internal Connector	LVDS & Inverter	1
	USB	4 (USB 2.0 compliant)
	Serial	4 (RS-232, COM3 support 5V/12V by jumper selection)
	IDE	None
	SATA	4
	CFast CompactFlash	1
	Parallel	None
Watchdog Timer	GPIO	8-bit
	Output	System reset
Power	Interval	Programmable 1 ~ 255 sec/min
	Power Type	Single voltage 12V DC input; 1 x External DC jack; 1 x Internal 4-pin (2x2) power connector; Supports AT/ATX mode
Environment	Power Consumption	12 V @ 2.97 A (AMD T56N 1.65 GHz processor/DDR3 1333 MHz 4 GB, SATA HDDx1) 12 V @ 1.36 A (AMD T40E 1.0 Hz processor/DDR3 1333 MHz 4 GB, SATA HDDx1)
	Temperature	Operating 0 ~ 60° C (32 ~ 140° F) Non-Operating -40 ~ 85° C (-40 ~ 185° F)
Physical Characteristics	Dimensions	170 mm x 170 mm (6.69" x 6.69")

Block Diagram



Ordering Information

Part Number	CPU	Display	LAN	COM	TPM	Thermal solution
AIMB-223G2-S2A2E	DC 1.65 GHz	CRT/LVDS/HDMI	2	6	1	Active

Note: Passive = fanless; Active = with fan

Packing List

Part Number	Description	Quantity
1700018785	SATA Power cable	2
1700003194	SATA HDD cable	2
1700008876	Serial port cable	2
1960046526N001	CPU cooler	1
1960058596T000	I/O port bracket	1
2006022310	Startup manual	1
2062022300	Driver CD	1

I/O View



AIMB-223G2-S2A2E

Optional Accessories

Part Number	Description
1700003195	USB cable with two ports, 17.5 cm
1700002204	USB cable with two ports, 27 cm
1700008461	USB cable with four ports, 30.5 cm
1757003064	Adapter AC100-240V, 84W, +12V/ 7A FSP
1757003995	Adapter AC100-240V, 60W, +12V/ 5A FSP

Optional Chassis

Part Number	Description
AIMB-B2000-00YE	Mini-ITX chassis with optional DC Adaptor

Embedded OS/API

OS/API	Part No.	Description
Win XPE	TBD	WES09 AIMB-223 V4.0 ENG ATIP
WES7	TBD	WES7E SP1 x32 AIMB-223 V5.1 ENG ATIP

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.