


AIMB-274


Intel® Core™ i7/i5/i3 LGA 1150 Mini-ITX
with VGA/DP⁺⁺/HDMI(DP⁺⁺)/LVDS(eDP),
2 COM, Dual LAN, PCIe x16

NEW



Specifications

Processor System	CPU	i7-4790S	i7-4770S	i7-4770TE	i5-4590S/4590T	i5-4570S	i5-4570TE	i3-4360/4350T/4340TE	i3-4330	i3-4330TE	Pentium G3420	Pentium G3320TE
	Core Number	4	4	4	4/4	4	2	2/2/2	2	2	2	2
	Max Speed	3.2GHz	3.1 GHz	2.3 GHz	3.0/2.0 GHz	2.9 GHz	2.7 GHz	3.7/3.1/2.6 GHz	3.5 GHz	2.4 GHz	3.2 GHz	2.3 GHz
	L3 Cache	8M	8M	8M	6M/6M	6M	4M	4M/4M/4M	4M	4M	3M	3M
	TDP (W)	65W	65W	45W	65W/35W	65W	35W	54W/35W/35W	54W	35W	54W	35W
	Chipset	Q87										
	BIOS	AMI EFI 128 Mbit SPI										
Expansion Slot	PCI	-										
	Mini-PCIe	2, F/S x 1 support mSATA, H/S x 1 with SIM card holder										
	PCIe x16 (Gen3)	16 GB/s per direction, 1 slot										
Memory	Technology	Dual Channel DDR3/DDR3L @ 1.5V 1333/1600 MHz SDRAM										
	Max. Capacity	16 GB (up to 8 GB per SO-DIMM)										
	Socket	2 x 204 Pin DDR3 SO-DIMM (Non-ECC)										
Graphics	Controller	Supports DirectX11.1, OpenGL 4.0 and OpenCL 1.2										
	VRAM	Shared system memory, 2 GB and above, total system memory shared 1 GB maximum video memory										
	CRT	Yes, supports max. resolution 1920 x 1200 @ 60 Hz										
	LVDS	Supports dual channel 48-bit up to 1920 x 1200										
	HDMI	Yes, supports max. resolution 1920 x 1200										
	eDP	Yes, with internal pin header, supports max. resolution 3840 x 2160 @ 60 Hz										
	Display Port 1.2	Yes, supports max. resolution 3840 x 2160 @ 60 Hz										
Ethernet	Triple Display	VGA+LVDS+HDMI, VGA+LVDS+DP, VGA+DP+HDMI, VGA+DP+DP, VGA+eDP+HDMI, VGA+eDP+DP, LVDS+DP+HDMI, LVDS+DP+DP, eDP+DP+HDMI, eDP+DP+DP										
	Interface	10/100/1000 Mbps										
	Controller	GbE LAN1: Intel I217LM; LAN2: Intel I211AT										
	Connector	RJ-45 x 2										
SATA	Max Data Transfer Rate	600 MB/s (SATA 3.0)										
	Channel	4										
Rear I/O	CRT	1										
	HDMI (DP ⁺⁺)	1, shared with DP by auto detection										
	Display Port 1.2	1										
	Ethernet	2										
	USB	4 (USB 3.0)										
	Audio	3 (Mic-in, Line-out, Line-in)										
	Serial	1 (RS-232, supports 5V/12V)										
Internal Connector	eSATA	1										
	USB	6 (USB 2.0)										
	LVDS/inverter	1										
	Serial	1 (RS-232/422/485)										
	IDE	-										
	SATA	4 (SATA 3.0)										
	Mini-PCIe	2 (F/S x 1 & H/S x 1)										
Watchdog Timer	Parallel	-										
	IrDA	-										
	GPIO	8-bit										
Power Requirements	Output	System reset										
	Interval	Programmable 1 ~ 255 sec/min										
Environment	Input power	ATX										
		Win Idle 18.725 W (Intel Core i7-4770S 3.1GHz / DDR3 1600MHz 8GB x 2)										
Physical Characteristics	Operating	Non-Operating										
	Temperature	0 ~ 60° C (32 ~ 140° F), depends on CPU speed and cooler solution -40 ~ 85° C (-40 ~ 185° F)										
Physical Characteristics	Dimensions	170 mm x 170 mm (6.69" x 6.69")										



Ordering Information

P/N	Chipset	DP	CRT	LVDS/eDP	HDMI/DP	GbE LAN	COM	eSATA	SATA	USB 3.0/2.0	MiniPCIe	TPM	AMP	PCIex16
AIMB-274G2-00A1E	Q87	1	1	1 (1)	1 (CEC)	2	2	1	4	4/6	2 (1 x F/S; 1 x H/S)	(1)	(1)	1
AIMB-274L-00A1E	Q87	0	1	0	1	1	2	0	2	4/6	1 (F/S)	0	0	1

*() BOM options available on MP version.

Packing List

Part Number	Description	Quantity
1700003194	SATA HDD cable	2 for G2 sku, 0 for L sku
1700018785	SATA power cable	2
1700001788	Serial port cable, 30cm	1
1960060539T000	I/O port bracket	1 for G2 sku
1960060539T100	I/O port bracket	1 for L sku
2006027410	Startup manual	1
2066027400	Driver CD	1

Optional Chassis

Part Number	Description
AIMB-B2000-15ZE	Mini-ITX chassis with 150W ATX power supply

I/O View



AIMB-274G2-00A1E



AIMB-274L-00A1E

Optional Accessories

Part Number	Description
1703100121	USB cable with two ports, 12 cm
1703100261	USB cable with two ports, 26 cm
1703100350	USB cable with two ports, 34.5 cm
1703060191	KB/MS cable 1*6P-2.0/M-DIN 6P(F)*2, 19cm
1960053207N001	LGA1150 CPU cooler for CPU TDP ≤ 65W, 92.9 (W) x 92.9 (L) x 46 (H) mm
1960060732N001	LGA1150 CPU cooler for CPU TDP ≤ 45W, 80 (W) x 80 (L) x 32.2 (H) mm

Note: Purchasing AIMB-274's proprietary CPU cooler from Advantech is a must, other brand's CPU cooler are NOT compatible with AIMB-274.

Embedded OS/API

OS/API	Part No.	Description
WES7	2070012179	WES7E AIMB-274 x86 V5.1.6 Eng/Jpn/Cht/Chn
WES8	2070012425	WES8E AIMB-274 x86 V6.0.0 Eng
iManager		Software APIs for hardware monitoring ,smart fan, watchdog, GPIO, brightness control

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.