

ADAM-4012

ADAM-4013

ADAM-4015

1-ch Analog Input Module

1-ch RTD Input Module


6-ch RTD Module with Modbus



ADAM-4012



ADAM-4013



ADAM-4015



Specifications

General

- Power Consumption 1.2 W @ 24 V_{DC}
- Supported Protocols ASCII command
- Connectors 1 x plug-in terminal block (#14 ~ 22 AWG)

Analog Input

- Channels 1
- Input Impedance Voltage: 20 M Ω
Current: 125 Ω (Added by user)
- Input Type mV, V or mA
- Input Range ± 150 mV, ± 500 mV, ± 1 V, ± 5 V, ± 10 V and ± 20 mA
- Accuracy Voltage mode: $\pm 0.1\%$ or better
Current mode: $\pm 0.2\%$ or better
- Span Drift ± 25 ppm/ $^{\circ}$ C
- Zero Drift ± 6 μ V/ $^{\circ}$ C

Digital Input

- Channels 1
Logic level 0: 1 V max.
Logic level 1: 3.5 ~ 30 V
pull up current: 0.5 mA,
10 k Ω resistor to 5 V
- Event Counter Max. input freq.: 50 Hz
Min. input pulse width: 1 msec.

Digital Output

- Channels 2, open collector to 30 V,
30 mA max. load
- Power Dissipation 300 mW

Specifications

General

- Power Consumption 0.7 W @ 24 V_{DC}
- Supported Protocols ASCII command
- Connectors 1 x plug-in terminal block (#14 ~ 22 AWG)

Analog Input

- Channels 1
 - Input Connections 2 or 3-wire
 - Input Impedance 2 M Ω
 - Input Type Pt or Ni RTD
 - RTD Types and Temperature Ranges
- | IEC RTD 100 ohms | | | | |
|------------------|-------------------|----|-------------------|-------------|
| Pt | -100 $^{\circ}$ C | to | +100 $^{\circ}$ C | a = 0.00385 |
| Pt | 0 $^{\circ}$ C | to | +100 $^{\circ}$ C | a = 0.00385 |
| Pt | 0 $^{\circ}$ C | to | +200 $^{\circ}$ C | a = 0.00385 |
| Pt | 0 $^{\circ}$ C | to | +600 $^{\circ}$ C | a = 0.00385 |
-
- | JIS RTD 100 ohms | | | | |
|------------------|-------------------|----|-------------------|--------------|
| Pt | -100 $^{\circ}$ C | to | +100 $^{\circ}$ C | a = 0.003916 |
| Pt | 0 $^{\circ}$ C | to | +100 $^{\circ}$ C | a = 0.003916 |
| Pt | 0 $^{\circ}$ C | to | +200 $^{\circ}$ C | a = 0.003916 |
| Pt | 0 $^{\circ}$ C | to | +600 $^{\circ}$ C | a = 0.003916 |
-
- | Ni RTD | | | | |
|--------|------------------|----|-------------------|--|
| Ni | -80 $^{\circ}$ C | to | +100 $^{\circ}$ C | |
| Ni | 0 $^{\circ}$ C | to | +100 $^{\circ}$ C | |
- Accuracy $\pm 0.1\%$ or better
 - Span Drift ± 25 ppm/ $^{\circ}$ C
 - Zero Drift ± 3 μ V/ $^{\circ}$ C
 - CMR @ 50/60 Hz 150 dB

Specifications

General

- Connectors 2 x plug-in terminal blocks (#14 ~ 28 AWG)
- Power Consumption 1.2 W @ 24 V_{DC}
- Watchdog Timer System (1.6 s) & Communication
- Supported Protocols ASCII command and Modbus/RTU
- Burn-out Detection Yes

Analog Input

- Channels 6 differential
 - Input Connections 2, 3-wire
 - Input Impedance 10 M Ω
 - Input Type Pt, Balco and Ni RTD
 - RTD Types and Temperature Ranges
- | Pt 100 RTD: | | | | |
|-------------|-------------------|----|------------------|--|
| Pt | -50 $^{\circ}$ C | to | 150 $^{\circ}$ C | |
| Pt | 0 $^{\circ}$ C | to | 100 $^{\circ}$ C | |
| Pt | 0 $^{\circ}$ C | to | 200 $^{\circ}$ C | |
| Pt | 0 $^{\circ}$ C | to | 400 $^{\circ}$ C | |
| Pt | -200 $^{\circ}$ C | to | 200 $^{\circ}$ C | |
-
- | IEC RTD 100 ohms (a = 0.00385) | | | | |
|--------------------------------|--|--|--|--|
| JIS RTD 100 ohms (a = 0.00392) | | | | |
-
- | Pt 1000 RTD | | | | |
|-------------|------------------|----|------------------|--|
| Pt | -40 $^{\circ}$ C | to | 160 $^{\circ}$ C | |
-
- | Balco 500 RTD | | | | |
|---------------|------------------|----|------------------|--|
| | -30 $^{\circ}$ C | to | 120 $^{\circ}$ C | |
-
- | Ni 50 RTD | | | | |
|-----------|------------------|----|------------------|--|
| Ni | -80 $^{\circ}$ C | to | 100 $^{\circ}$ C | |
-
- | Ni 508 RTD | | | | |
|------------|----------------|----|------------------|--|
| Ni | 0 $^{\circ}$ C | to | 100 $^{\circ}$ C | |
-
- | BA1 | | | | |
|-----|-------------------|----|------------------|--|
| | -200 $^{\circ}$ C | to | 600 $^{\circ}$ C | |
- Accuracy $\pm 0.1\%$ (Typical)
 - CMR @ 50/60 Hz 120 dB
 - Span Drift ± 25 ppm/ $^{\circ}$ C
 - Zero Drift ± 3 μ V/ $^{\circ}$ C

Common Specifications

General

- Power Input Unregulated 10 ~ 30 V_{DC}
- Connectors 1 x plug-in terminal block (#14 ~ 22 AWG)
- Watchdog Timer System (1.6 second)

Analog Input

- Resolution 16-bit
- Sampling Rate 10 sample/second (total)

- NMR @ 50/60 Hz 100 dB
- Isolation Voltage 3,000 V_{DC}

Environment

- Operating Humidity 5 ~ 95% RH
- Operating Temperature -10 ~ 70 $^{\circ}$ C (14 ~ 158 $^{\circ}$ F)
- Storage Temperature -25 ~ 85 $^{\circ}$ C (-13 ~ 185 $^{\circ}$ F)

Ordering Information

- ADAM-4012 1-ch Analog Input Module
- ADAM-4013 1-ch RTD Input Module
- ADAM-4015 6-ch RTD Module with Modbus

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.