

EKI-5626C/I-PN

EKI-5629C/I-PN

16 + 2G Combo Ports Entry-Level Managed Switch Supporting PROFINET

8 + 2G Combo Ports Entry-Level Managed Switch Supporting PROFINET



EKI-5626C/I-PN

EKI-5629C/I-PN



Features

- 16 Fast Ethernet ports + 2 Gigabit Copper/SFP combo ports (EKI-5626C/I-PN) & 8 Fast Ethernet ports + 2 Gigabit Copper/SFP combo ports (EKI-5629C/I-PN)
- Entry-Level Managed Switch
- IXM function enables fast deployment
- Provides GSDML files
- Management: SNMP v1/v2c/v3, WEB, Standard MIB, Private MIB
- Supports Media Redundancy Protocol (MRP slaves)

Introduction

EKI-5626C/5629C-PN are new generation of entry-level managed switch products. They support media redundancy protocols and meet the PROFINET real time standard. The devices come with a compact metal housing that is IP30 rated to protect against dusty industrial environments. The wide power input power (8.4 to 52.8 V_{DC}) is dedicated to operating in areas of unstable power and rugged environments.

Specifications

Communications

- Standard** IEEE 802.3, 802.3u, 802.3x, 802.1D, 802.1w, 802.1p, 802.1Q, 802.1X, 802.3AD, 802.3az, 10/100Base-T (X),
- LAN**
- Transmission Distance** Ethernet: UP to 100m (4-wire Cat.5e, Cat.6 RJ-45 cable suggested for Gigabit port)
SFP: UP to 110km (depends on SFP)
- Transmission Speed Ethernet** Ethernet: 10/100Mbps Auto-Negotiation
Gigabit Copper: 10/100/1000Mbps, Auto-Negotiation
Gigabit Fiber: UP to 1000Mbps

Interface

- I/O Port** EKI-5626C/I-PN: 16 x RJ-45 + 2 x RJ-45/SFP combo ports
EKI-5629C/I-PN: 8 x RJ-45 + 2 x RJ-45/SFP combo ports
- Power Connector** 6-pin screw Terminal Block (including relay)

Physical

- Enclosure** Metal Shell
- Protection Class** IP 30
- Installation** DIN-Rail
- Dimensions (W x H x D)** 74 x 120 x 84 mm

LED Display

- System LED** PWR1, PWR2, P-Fail, Loop/Status
- Port LED** Link / Speed / Activity

Environment

- Operating Temperature** EKI-5626C/I-PN & EKI-5629C/I-PN: -40 ~ 75°C (-40 ~ 167°F)
EKI-5626C-PN & EKI-5629C-PN: -10 ~ 60°C (14 ~ 140°F)
- Storage Temperature** -40 ~ 85°C
- Ambient Relative Humidity** 10 ~ 95% (non-condensing)
- Humidity** 10 ~ 95% (non-condensing)
- MTBF** EKI-5626C/I-PN: 2,825,281 hours
EKI-5629C/I-PN: 3,183,604 hours

Power

- Power Consumption** EKI-5626C/I-PN: Max 8.2W
EKI-5629C/I-PN: Max 5.8W
- Power Input** 12 ~ 48 V_{DC} (8.4~52.8 V_{DC}), redundant dual power input
- Fault Output** 1 Relay Output

Certification

- EMI** CE, FCC Class A
- Safety** UL508, Class 1 Division 2, ATEX
- EMC** EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-8
- Shock** IEC 60068-2-27
- Freefall** IEC 60068-2-32
- Vibration** IEC 60068-2-6

L2 Features

- L2 MAC Address** 8K
- Jumbo Frame** 9216 Bytes
- VLAN Group** 256 (VLAN ID 1~4094)
- VLAN Arrange** Port based VLAN, GVRP
- Port Mirroring** Per port, Multi-source port, IGMP Snooping v1/v2/v3, MLD Snooping, IGMP Immediate leave
- IP Multicast** Broadcast, Multicast, Unknown unicast
- Storm Control** IEEE 802.1D-STP, IEEE 802.1s-MSTP, IEEE 802.1w-RSTP, X-Ring, with ultra high-speed recovery time less than 20ms
- Redundancy**

QoS

- Priority Queue Scheduling** WRR (Weighted Round Robin), SP (Strict Scheduling Priority) Hybrid Priority
- Class of Service** IEEE 802.1p Based CoS, IP TOS, DSCP based CoS
- Rate Limiting** Ingress Rate limit, Egress Rate limit
- Link Aggregation** IEEE 802.3ad Dynamic Port Trunking, Static Port Trunking


Security

- Port Security** Static, Dynamic, MAC address filtering
- Authentication** 802.1x (Port-Based, MD5/TLS/TTL/PEAP Encryption)


Dimensions

Unit: mm [inch]

EKI-5626C/I-PN



EKI-5629C/I-PN



Management

- **Access** SNMP v1/v2c/v3, WEB, Standard MIB, Private MIB
- **Software upgrade** TFTP, HTTP, Dual Image
- **NTP** SNTP client
- **Data** Syslog
- **Protocols** IPV6, LLDP, PROFINET, Media Redundancy Protocol

Ordering Information

- **EKI-5626C-PN-AE** 16 + 2G Combo ports entry-level managed switch support PROFINET
- **EKI-5626CI-PN-AE** 16 + 2G Combo ports entry-level managed switch support PROFINET w/wide temp.
- **EKI-5629C-PN-AE** 8 + 2G Combo ports entry-level managed switch support PROFINET
- **EKI-5629CI-PN-AE** 8 + 2G Combo ports entry-level managed switch support PROFINET w/wide temp.

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.