

MIC-1816

16-Bit, 1MS/s, 16-Ch DAQ Platform with Intel® Core™ i3*/Celeron® Processor

NEW



Features

- 16 x Analog inputs, up to 1 MS/s, 16-bit resolution
- 2 x Analog outputs, up to 3 MS/s, 16-bit resolution
- Supports digital and analog triggers
- 16 x Isolated digital input, 8 isolated digital output
- 2 x 32-bit programmable counter/timers
- Onboard FIFO memory (4,096 samples)
- 2 x RS-232 ports
- 2 x 10/100/1000 Base-T RJ-45 LAN ports
- 2 x USB 2.0 and 2 x USB 3.0 ports
- iDoor expansion supported

Introduction

MIC-1816 is a stand-alone automation controller featuring an integrated DAQ module and signal conditioning to provide digital I/O, analog I/O, and counter functions. This application-ready controller also supports serial communication ports and several other networking interfaces to enable seamless integration and rapid system development.

Specifications

Analog Input

- Channels** 16-ch single ended, 8-ch differential
- Resolution** 16 bits
- Sample Rate** Single channel: 5 MS/s max.; Multiple channels: 1 MS/s max.

Note: The sampling rate of each channel is influenced by the number of used channels. For example, if 4 channels are used, the sampling rate will be 1MS/4 = 250 kS/s per channel.

- Trigger Reference** Digital and analog triggers
- Trigger Mode** Start, Delayed Start; Stop, Delayed Stop
- FIFO Size** 4,096 samples
- Overvoltage Protection** 30 Vp-p
- Input Impedance** 1 GΩ
- Sampling Modes** Software and external clock
- Input Range** Software programmable

Gain	0.5	1	2	4	8
Unipolar	NA	0-10	0-5	0-2.5	0-1.25
Bipolar	±10, 0-20mA, 4-20mA	±5	±2.5	±1.25	±0.625
Gain Error (%FSR)	Voltage: 0.0075 Current: 0.03	0.0075	0.01	0.02	0.03

Analog Output

- Channels** 2
- Resolution** 16 bits
- Sample Rate** 3 MS/s max.
- Output Range** Software programmable

Output Range	Internal Reference	0V-5V, 0V-10V, ±5V, ±10V	
	External Reference	Reference Input	Maximum Range
	Unipolar	-10V ≤ x ≤ 10V	
	Bipolar	-x V ~ x V	

Isolated Digital Input

- Channels** 16
- Input Voltage** Logic 0: 3 V max. Logic 1: 10 V min. (30 V max.)
- Interrupt Capable Ch.** 2 (IDIO & IDI8)
- Isolation Protection** 2,500 V DC
- Opto-Isolator Response** 100 μs
- Input Resistance** 3.2 kΩ @ 1 W

Isolated Digital Output

- Channels** 8
- Output Type** Sink (NPN)
- Output Voltage** 5 ~ 40V_{DC}
- Sink Current** 350mA max./channel @ 25°C, 250mA max./channel @ 60°C
- Isolation Protection** 2,500 V DC
- Opto-Isolator Response** 100 μs

Counter

- Channels** 2
- Resolution** 32 bits
- Compatibility** 5 V/TTL
- Max. Input Frequency** 10 MHz
- Pulse Generation** Yes
- Timebase Stability** 50 ppm

General

- Dimensions (W x H x D)** 200 x 156 x 58 mm (7.87" x 6.14" x 2.28")
- Power Consumption** Typ.: 12.24W @ 24V, Max.: 50W @ 24V
- Power Requirements** 10 ~ 36 V_{DC}
- Weight** 2.4 kg (typical)
- OS Support** Up to Windows 10 / Linux

System Hardware

- CPU** Intel® Celeron® 3955U processor, 2.0 GHz (MIC-1816-U0A1E) Intel® Core™ i3-6100U processor, 2.3 GHz (MIC-1816-U3A1E*)
- Memory** 4G DDR3 (Max. 16GB expansion available)
- Indicators** LEDs for Power, IDE and LAN (Active, Status)
- USB** USB 2.0 *2, USB 3.0 *2
- Storage** 1 x 2.5" HDD/SSD, installation subject to ordered configuration
- Expansion** Mini PCIe full size *1 (iDoor)

Environment

- Storage Humidity** 5 ~ 95% RH, non-condensing
- Operating Temperature** -20 ~ 60 °C (-4 ~ 140 °F) @ 5 ~ 85% RH with 0.7m/s air flow
- Storage Temperature** -20 ~ 80 °C (-4 ~ 176 °F)

Ordering Information

- MIC-1816-U0A1E** DAQ platform with Intel® Celeron® 3955U processor
- MIC-1816-U3A1E*** DAQ platform with Intel® Core™ i3-6100U processor

Optional Accessories

- 1960099348N001** Table mount (220 x 156 mm)
- PSD-A60W24** DIN Rail AC to DC 100-240V 60W 24V

* Supported by request; please contact Advantech if this is needed.

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.