

# FPM-212 FPM-215 FPM-217 FPM-219

## 12" XGA/15" XGA/17" SXGA/19" SXGA Industrial Monitors with Resistive Touch Control, Direct HDMI, DP, and VGA Ports



### Features

- 12" XGA/17" SXGA TFT LED LCD with 50,000 backlight lifetime
- 15" XGA/19" SXGA TFT LED LCD with 70,000 backlight lifetime
- Direct HDMI, DP and VGA input interfaces
- Anti-glare screen with tempered glass
- Robust system with Die-casting aluminum chassis and IP66-rated aluminum alloy front bezel
- Lockable I/O connectors
- Slim design enables easy installation
- Supports various mount options: panel, desktop, and VESA arm

### Introduction

In IIoT and Industry 4.0, more and more customers need data to be visualized to help process management and decision making. The FPM-200 series is an industrial-grade monitor with sleek, simple lines and a true-flat touchscreen. Equipped with durable resistive touch control and an IP66-rated front bezel, FPM-200 series is designed for intuitive operation in industrial environments such as smart factory and machine automation display applications.

### Specifications

#### General

- **Certification** BSMI, CCC, CE, FCC Class A, UL
- **Dimensions (W x H x D)**
  - FPM-212: 311.8 x 238.0 x 53 mm (12.27 x 9.37 x 2.08 in)
  - FPM-215: 383.2 x 307.3 x 53.20 mm (15.08 x 12 x 2.09 in)
  - FPM-217: 410.4 x 343.4 x 54 mm (16.15 x 13.51 x 2.12 in)
  - FPM-219: 454 x 379.8 x 51.5 mm (17.87 x 14.95 x 2.03 in)
- **Enclosure** Front panel: Die cast magnesium alloy  
Rear cover: Die-casting aluminum
- **Mount Options** Stand, Wall, Panel and VESA arm (75 x 75mm)
- **Power Input** FPM-2XX-R8AE : External 36 W power adapter, with AC 100 V ~ 240 V input and DC +12 V @ 3 A output (included)  
FPM-2XX-R9AE: Terminal Block: 24 V<sub>DC</sub> input, (Optional 60W power adapter)
- **Video Port** HDMI, DP, and VGA
- **Weight (Net)** 3.2 kg / 4.6 kg / 5.4 kg / 6.2 kg

#### Power Consumption

- **FPM-212-R8AE** 17.91(idle), 19.01(Max)
- **FPM-215-R8AE** 14.69(idle), 15.32(Max)
- **FPM-217-R8AE** 12.04(idle), 14.56(Max)
- **FPM-212-R9AE** 16.65(idle), 17.51(Max)
- **FPM-215-R9AE** 14.19(idle), 14.75(Max)
- **FPM-217-R9AE** 11.92(idle), 14.19(Max)
- **FPM-219-R9AE** 14.19(idle), 15.53(Max)

#### LCD Display

- **Display Type** XGA/XGA/SXGA/SXGA TFT LCD
- **Display Size** 12"/15"/17"/19"
- **Max. Resolution** 1024 x 768/1024 x 768/1280 x 1024/1280 x 1024
- **Max. Color** 16.2M/16.2M/16.7M/16.7M
- **Viewing Angle (H/V °)** 178/178, 176/176, 170/160,170/160
- **Luminance (cd/m<sup>2</sup>)** 600/300/250/350
- **Backlight Life** 50,000/70,000/50,000/70,000 hr
- **Contrast Ratio** 1000:1 / 2000:1 / 1000:1/1000:1

#### Touchscreen


- **Type** 5-wire analog resistive
- **Interface** USB
- **Light Transmission** Above 75%
- **OS Support** Windows XP, Vista,7, 8,10,XPe and Linux

#### Environment

- **Operating Temperature** 0 ~ 50 °C (32 ~ 122 °F)
- **Storage Temperature** -20 ~ 60 °C (-4 ~ 140 °F)
- **Humidity (Storage)** 10 ~ 90% non-condensing
- **IP Rating** IP-66 graded front panel
- **Vibration** 5 ~ 500 Hz, 1 Grms (Operating, Random)

## Dimensions

Unit: mm



**Panel Cutout Dimensions:** FPM-212: 303 x 229 mm (11.93 x 9.02 in)  
 FPM-215: 374.5 x 298.5 mm (14.74 x 11.75 in)  
 FPM-217: 401.3 x 334.8 mm (15.8 x 13.18 in)  
 FPM-219: 443.5 x 369.3 mm (17.46 x 14.53 in)

## Ordering Information

- **FPM-212-R8AE** 12.1" XGA Ind. Monitor, w/Resistive TS
- **FPM-215-R8AE** 15 XGA Ind. Monitor, w/Resistive TS
- **FPM-217-R8AE** 17" SXGA Ind. Monitor, w/Resistive TS
- **FPM-212-R9AE** 12.1" XGA Ind. Monitor, w/Resistive TS (24 V<sub>DC</sub>)
- **FPM-215-R9AE** 15 XGA Ind. Monitor, w/Resistive TS (24 V<sub>DC</sub>)
- **FPM-217-R9AE** 17" SXGA Ind. Monitor, w/Resistive TS (24 V<sub>DC</sub>)
- **FPM-219-R9AE** 19" SXGA Ind. Monitor, w/Resistive TS (24 V<sub>DC</sub>)
- **96PSA-A60W24T2-3** Adapter 100-240V 60W 24V (Optional for 24 V<sub>DC</sub> models only)

## Front View




## Optional Accessories


- **1700001524** Power Cable US Plug, 1.8m
- **170203183C** Power Cable EU Plug, 1.8m
- **170203180A** Power Cable UK Plug, 1.8m
- **1700008921** Power Cable JP Plug, 1.8m
- **1700019146** Power Cable China/Australia Plug, 1.8m
- **FPM-1000T-SMKE** Desktop/Wall Mounting kit for FPM series

## I/O View

I/O View (12VDC)




I/O View (24VDC)




## Rear View

Rear View (12VDC)



Rear View (24VDC)



# Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



## AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 [www.autocont-ipc.cz](http://www.autocont-ipc.cz)



### PRŮMYSLOVÉ POČÍTAČE

*fanless embedded PC, do racku, ...*



### POČÍTAČE S DISPLEJEM

*panelové PC, terminály, do vozidel, ...*



### AUTOMATIZACE A SBĚR DAT

*převodníky, karty, moduly, switche, ...*



### PERIFERIE A KOMPONENTY

*monitory, klávesnice, desky, skříně, ...*



### NOTEBOOKY A TABLETY

*odolné, windows, android, IP65, ...*



### INFORMAČNÍ KIOSKY

*interiérové, venkovní, ...*



### MEDICÍNSKÁ TECHNIKA

*počítače, tablety, LCD, klávesnice, ...*



### SOFTWAREVÁ ŘEŠENÍ

*pro výrobu, zaměstnance, kiosky, ...*



### PŘEJÍT DO E-SHOPU

[eshop.autocont-ipc.cz](http://eshop.autocont-ipc.cz)



### DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



### PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



### ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



### SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.