

EKI-2705G-1GPI

EKI-2705E-1GPI

4GE PoE + 1GE Unmanaged Industrial Switch

4FE PoE + 1GE Unmanaged Industrial Switch

Preliminary



EKI-2705G-1GPI

EKI-2705E-1GPI



Features

- Supports 10/100/1000Mbps auto negotiation (EKI-2705G)
- Supports jumbo frame transmission up to 9k bytes
- DIN-rail with IP30 metal mechanism
- Redundant 24 ~ 48 V_{DC} power input
- 4 x IEEE 802.3 af/at PoE /PoE+ ports & 1 x Giga (Fast Ethernet) Copper ports

Introduction

The EKI-2705 series supports 24 ~ 48V_{DC} redundant power input and is secured with a double protection mechanism: power polarity reverse protection and an overload current fuse. The EKI-2705 series supports up to 4-port IEEE 802.3 af/at PoE /PoE+ ports. Each port of EKI-2705 has two LED indicators to show the link status transmission speed. It also provides a relay output for an event alarm. In the event of a power failure, the built-in LED will activate the alarm to notify, administrators. Engineers can simply verify the hardware status by checking the LED to make troubleshooting easily and fast. EKI-2705 comes with a compact metal housing rated at IP30 to protect against dusty industrial environments.

Specifications

Communications

- **Standard** IEEE 802.3, 802.3u, 802.3x, 802.3ab, 802.3z
- **LAN** EKI-2705G-1GPI: 5 x 10/100/1000Mbps (RJ-45)
EKI-2705E-1GPI: 4 x 10/100Mbps (RJ-45) + 1 x 10/100/1000Mbps(RJ-45)
- **Transmission Distance** Ethernet: Up to 100 m (4-wire Cat.5e, Cat.6 RJ45 cable)
- **Transmission Speed** Gigabit Copper: 10/100/(1000) Mbps, Auto-Negotiation

Interface

- **Connectors** 5 x RJ-45
6-pin removable screw terminal (power & relay)
- **LED Indicators** P1, P2, P-Fail
Link / Speed / Activity/ POE

Power

- **Power Consumption** Max. 2 W
- **Power Input** 24 ~ 48 V_{DC}
- **Input current** 1.92A @ 48 V_{DC}
4.12A @ 24 V_{DC}
- **Fault Output** 1 Relay Output, 1 A @ 24 V_{DC}
- **Power Budget** 60W @ 75°C
90W @ 60°C

Mechanism

- **Dimensions (W x H x D)** 30 x 140 x 95 mm (1.18" x 5.51" x 3.74")
- **Enclosure** IP30, metal shell with solid mounting kits
- **Mounting** DIN-rail, Wall

Protection

- **Power Reverse** Present
- **Overload current** Present

Environment


- **Operating Temperature** -40 ~ 75 °C (-40 ~ 167 °F)
- **Storage Temperature** -40 ~ 85 °C (-40 ~ 185 °F)
- **Operating Humidity** 10 ~ 95% (non-condensing)
- **Storage Humidity** 10 ~ 95% (non-condensing)
- **MTBF** 1,697,086 hours

Certification

- **Safety** UL 62368, e-Mark(pending)
- **EMI** CE, FCC Class A
- **EMS** EN 61000-4-2
EN 61000-4-3
EN 61000-4-4
EN 61000-4-5
EN 61000-4-6
EN 61000-4-8
- **Shock** IEC 60068-2-27
- **Freefall** IEC 60068-2-32
- **Vibration** IEC 60068-2-6
- **Patent** <http://www.advantech.com/legal/patent>

Dimensions

Unit: mm [inch]



Ordering Information

- **EKI-2705G-1GPI-A** 4GE PoE + 1GE Unmanaged Industrial Switch w/Wide temp.
- **EKI-2705E-1GPI-A** 4FE PoE + 1GE Unmanaged Industrial Switch w/Wide temp.

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.