

# UNO-348

**Compact Embedded Edge Controller with 10th Gen Intel® Processor, up to 3 x PCIe/PCI slots, 1 x M.2 B-Key, 1 x mPCIe, and 2 x 2.5" SSD**

**NEW**



UNO-348-AXX1A

UNO-348-AXX3A



## Features

- 10th gen Intel® socket-type processor with DDR4 memory
- Scalable processor and RAM memory options
- Compact, rugged, fanless design for harsh embedded environments
- Flexible expansion with up to 3 x PCIe/PCI slots, 1 x M.2 (B-key), 1 x mPCIe, and 2 x 2.5" SSD
- Optional iDoor expansion
- Remote out-of-band (OOB) power management with Advantech's iBMC technology
- Built-in TPM2.0 for hardware-based security

## Introduction

UNO-348 is a high-performance, fanless, embedded edge controller equipped with a 10th gen. Intel® Core™ i5/i9 processor with 8/16 GB DDR4 memory and Intel® H420E PCH chipset. Despite its compact size, UNO-348 offers multiple I/O including 4 x USB 3.2, 2 x USB 2.0, 3 x GigaLAN, 2 x RS-232/422/485, and 1 x RS-232 ports, as well as 1 x Line-out, 1 x Mic-in, 1 x DisplayPort, and 1 x HDMI interfaces. Designed to deliver high-performance computing and maximum flexibility for industrial automation applications, UNO-348 also features 2 x internal HDD/SSD bays, 1 x full-size mPCIe, 1 x M.2 B-key, and up to 3 x PCIe/PCI expansion slots (1 x PCIe x16, 2 x PCI) to support the integration of optional peripherals. In addition to dual power inputs that ensure a stable power supply, UNO-348 is equipped with Advantech's iBMC technology to support remote OOB power management to reduce system downtime and operational costs.

## Specifications

### General

- **Certification** CB/UL, CE/FCC Class A, CCC, BSMI
- **Dimensions (W x D x H)** UNO-348-AXX1A: 200 x 140 x 120 mm/7.8 x 5.5 x 4.7 in  
UNO-348-AXX3A: 200 x 140 x 160 mm/7.8 x 5.5 x 6.3 in
- **Form Factor** Regular
- **Mounting** Wall, stand
- **Weight (Net)** UNO-348-AXX1A: 3.5 kg/7.7 lb  
UNO-348-AXX3A: 4 kg/8.8 lb
- **Power Requirements** 10 ~ 36 V<sub>DC</sub>  
Note: Power should be fixed at 24V<sub>DC</sub> (± 20%) when total power consumption exceeds 160W.
- **Power Consumption** 59W (typical), 100W (Max)  
When equipped with PCI/PCIe card:  
UNO-348-AXX1A: up to 174.1W  
UNO-348-AXX3A: up to 224.1W  
Note:  
PCIex16 slot supports up to 75W  
PCIex4 slot supports up to 25W  
PCIex1 slot supports up to 10W  
PCI slot supports up to 25W
- **OS Support** Windows 10 2019 LTSC, Windows 11, AdvLinux (Ubuntu 18.04)

### Hardware

- **BIOS** AMI UEFI (128 Mbit)
- **Hardware Security** TPM2.0
- **Watchdog Timer** Programmable timer with 255 intervals (1 ~ 255 sec)
- **Processor\*** Intel® Core™ i5-10500TE, 2.3 GHz, 6 cores  
Intel® Core™ i9-10900TE, 1.8 GHz, 10 cores  
Intel® H420E (W480E available upon request)
- **Chipset** i5 CPU: Built-in 8 GB DDR4, 2933 MHz, dual sockets support up to 64 GB  
i9 CPU: Built-in 16 GB DDR4, 2933 MHz, dual sockets support up to 64 GB
- **Graphics Engine** Intel HD Graphics
- **Ethernet** LAN A: Intel® i211-AT GbE, IEEE 802.3AZ/802.1AS  
LAN B: Intel® i210-AT GbE, IEEE 802.3AZ/802.1AS (Support iBMC)  
LAN C: Intel® i219-LM GbE, IEEE 802.3AZ/802.1AS

- **LED Indicators** 1 x Programmable LED, 1 x power LED, 1 x HDD LED, and 1 x LAN (active, status)
- **Storage/Expansion** 2 x 2.5" SSD/HDD bay (RAID is only supported by W480 chipset version upon request)  
1 x M.2 B key (SATA/ USB 3.0 signal) for 2242/2280 SATA SSD or 3042/3052 LTE/5G module expansion  
1 x Full-size mPCIe (PCIe/USB2.0 signal)  
UNO-348-AXX1A: 1 x PCIex16,  
UNO-348-AXX3A: 1 x PCIex16, 2 x PCI

### I/O

- **Serial Ports** 2 x RS-232/422/485, 1 x RS-232. 50bps ~115.2 kbps (DB9)
- **LAN Ports** 3 x RJ45, 10/100/1000 Mbps IEEE 802.3u 1000BASE-T Fast Ethernet
- **USB Ports** 4 x USB 3.2 Gen 1, 2 x USB 2.0 (Type A)
- **Displays** 1 x DP 1.4, supports 4096 x 2304 @ 60Hz (DP++)  
1 x HDMI 1.4, supports 4096 x 2160 @ 30Hz
- **Audio** Mic-in, Line-out (Line-out can be configured as Line-in upon request)
- **Power Connector** 1 x 4-pin terminal block
- **Remote Power Control** 1 x 2-pin terminal block that supports remote Power On/Off function (can support remote reset function via jumper settings)
- **GPIO** 1 x GPIO (8 bit) internal pin header


### Environmental

- **Operating Temperature** -20 ~ 50 °C/-4 ~ 122 °F with 0.7m/s airflow and wide-temperature (-40 ~ 85 °C/-40 ~ 185 °F) peripherals, e.g., SSDs, wireless modules
- **Storage Temperature** -40 ~ 85 °C/-40 ~ 185 °F
- **Relative Humidity** 95% RH @ 40 °C/104 °F, non-condensing
- **Shock Protection** Operating, IEC 60068-2-27, 50G, half sine, 11ms
- **Vibration Protection** Operating, IEC 60068-2-64, 4 Grms, random, 5 ~ 500 Hz, 1hr/axis (SSD)
- **Ingress Protection** IP20


\*The processor and memory can be flexibly configured. See ordering information for more details.

# Installation Options

## Stand mount



## Wall mount











Note: Mount kit included with product as a default.



## Dimensions

Unit: mm

### UNO-348-AXX1A











Stand Mount





Wall Mount

### UNO-348-AXX3A




Stand Mount




Wall Mount

## I/O View

### UNO-348-AXX1A



### UNO-348-AXX3A



## Ordering Information

Part Number	Description	CPU	PCH	RAM	Number of PCIe/PCI Slots
UNO-348-A531A	Intel® Core™ i5-10500TE 6-core CPU, Intel® H420E chipset, 8 GB RAM, 3 x COM, 6 x USB, 3 x LAN, 1 x PCIe x16	Intel® Core™ i5-10500TE	H420E	8 GB	1 x PCIe x16
UNO-348-A941A	Intel® Core™ i9-10900TE 10-core CPU, Intel® H420E chipset, 16 GB RAM, 3 x COM, 6 x USB, 3 x LAN, 1 x PCIe x16	Intel® Core™ i9-10900TE		16 GB	
*UNO-348-ANN1A	Intel® H420E chipset, 3 x COM, 6 x USB, 3 x LAN, 1 x PCIe x16	Optional. (Supports Intel® Core™ i9/i7/i5/i3/Celeron®/Pentium®)		Optional support up to 64 GB	
UNO-348-A533A	Intel® Core™ i5-10500TE, 6-core CPU, Intel® H420E chipset, 8 GB RAM, 3 x COM, 6 x USB, 3 x LAN, 1 x PCIe x16, 2 x PCI	Intel® Core™ i5-10500TE	H420E	8 GB	1 x PCIe x16, 2 x PCI
UNO-348-A943A	Intel® Core™ i9-10900TE 10-core CPU, Intel® H420E chipset, 16 GB RAM, 3 x COM, 6 x USB, 3 x LAN, 1 x PCIe x16, 2 x PCI	Intel® Core™ i9-10900TE		16 GB	
*UNO-348-ANN3A	Intel® H420E chipset, 3 x COM, 6 x USB, 3 x LAN, 1 x PCIe x16, 2 x PCI	Optional. (Supports Intel® Core™ i9/i7/i5/i3/Celeron®/Pentium®)		Optional support up to 64 GB	

\*For this model, the processor and RAM memory must be ordered separately.

## Optional Expansion

### PCIe/PCI Backplane (for UNO-348-AXX3A)

- **9893UR05000** 1 x PCIe x16, 2 x PCIe x1

### RAM

- **SQR-SD4N8G3K2SNBCB** SODIMM DDR4 3200 8GB
- **SQR-SD4N16G3K2SNCB** SODIMM DDR4 3200 16GB
- **SQR-SD4N32G3K2SNAB** SODIMM DDR4 3200 32GB

### iDoor Module

Please purchase an additional iDoor PCIe I/O plate for iDoor module installation.

- **PCM-28P1BK-AE** iDoor PCIe I/O plate

Note:

1. The iDoor I/O plate will occupy one of PCIe/PCI slot
2. Contact Advantech information about supported iDoor modules.

### GPIO cable

- **1700030635-01** D-SUB 9Pin GPIO cable 15cm

Note: Need to swap 1 x RS-232 to GPIO

## Optional Accessories

### Power Supply

- **96PSA-A230W24P4-3** ADP A/D 100 ~ 240V 230W 24V C14 4P terminal block

### Power Cable

- **1702002600** Power cable (USA) UL/CSA, 3-pin, 10A, 125V, 1.83M
- **1702002605** Power cable (EU), 3-pin, 10A, 250V, 1.83M
- **1700000596** Power cable CCC, 3-pin, 10A, 250V, 1.83M

### Wireless Solution

- **AIW-355DQ-C01** 5G(Sub-6G)/LTE/WCDMA module, GNSS, for China
- **AIW-355DQ-E01** 5G(Sub-6G)/LTE/WCDMA module, GNSS, for Europe
- **AIW-355DQ-N01** 5G(Sub-6G)/LTE/WCDMA module, GNSS, for US
- **UNO-M2-3052HS** M.2B 3052 Heatsink for AIW-355 5G module
- **1750008879-01** Cable Ant. SMA/F-BH MH4/113 BLK L150mm
- **1750009372-01** Dipole antenna, 5G(Sub-6G)/LTE/WCDMA full band, 167mm

## Embedded O/S

- **20704WX9HS0000** Win10 LTSC x64 v6.07 B008 for UNO-348 (High End)
- **20704WX9VS0000** Win10 LTSC x64 v6.07 B008 for UNO-348 (Value)
- **20704U20DS0004** AdvLinuxTU Embedded Linux x86\_64 v3.1.1

Caution: If the system is equipped with optional modules, additional certificates may be required in certain regions/countries. Contact Advantech for certification compliance.

# Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



## AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 [www.autocont-ipc.cz](http://www.autocont-ipc.cz)



### PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



### POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



### AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



### PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



### NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



### INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



### MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



### SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



### PŘEJÍT DO E-SHOPU

[eshop.autocont-ipc.cz](http://eshop.autocont-ipc.cz)



### DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



### PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



### ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



### SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.