

# ITA-260

## 11th Generation Intel® Core™ Processor Fanless System for Wayside & Roadside Applications



### Features

- Industrial-grade DIN rail fanless wayside & roadside appliances
- 11th Generation Intel® Core™ processor family
- 2 x SO-DIMM , up to 64G
- Supports 6 GbE (4 x RJ-45 & 2 x SFP)
- Supports 4 USB (2 x USB3.0 & 2 x USB2.0), 2 COM (isolated)
- 1 x 2.5" SATA SSD bay (easy swap)
- Supports LAN surge ± 2KV
- Supports Time-Sensitive Technology (TSN)
- Wide operating temperature -40 ~ 60 °C
- Compliant: EN50121-4
- Supports 9-48V wide-range DC input



### Introduction

ITA-260 is a fanless edge AI computing platform for intelligent transportation applications, especially for wayside monitoring on railway networks such as electricity power monitoring, railway track status monitoring, undercarriage track inspection, and wayside surveillance. ITA-260 helps railway operators achieve diagnostic maintenance, predictive maintenance, and remote management, greatly reducing management costs.

#### The featured highlights include


1. Compact size design for easy installation and maintenance in space-limited environments.
2. Supports the latest 11th Generation Intel® Core™ i Processor with improved performance.
3. Ruggedized design, withstand shock and vibration is ideal for harsh environments.
4. High expandability for diverse customization.

### Specifications


Processor System	CPU	11th Generation Intel® Core™ i3/i5/i7 Processor
	Max. Processor Base Frequency	3.0GHz
	L2 Cache	12MB
	BIOS	AMI EFI 16 Mbit
Memory	Technology	Dual channel DDR4 2400/2666/3200 MHz SO-DIMM/Wide temp
	Socket	2 x 266-pin SODIMM
	Capacity	SO-DIMM (up to 64GB with 2 slots)
Ethernet	Interface	100/1000/2500 Mbps
	Controller	2 x Intel I226-LM
		2 x Intel i210AT
		2 x Intel i210IS
	TSN	2 x RJ-45 Support
Connector	4 x RJ-45 & 2 x SFP	
Storage	2.5" SSD	1 x 2.5" SSD
	mSATA SSD	1 x mSATA Slot
I/O Interface	SATA	1 x SATA
	USB	2 x USB3.0
		2 x USB2.0
	LAN	4 x RJ-45 & 2 x SFP
	Serial port	2 x DB9 RS-232/422/485
Display	1 x HDMI	
Expansion	Expansion slots	1 x Mini PCIe (on the motherboard)
		2 x M.2 (1 x M.2 B key for 2280 & 1 x M.2 M key for 2280) or 2 x Mini PCIe (on the extended board)
Power	Input	DC 9-48V
	Connector	Phoenix contact 4-pin connector w/ lock
Environment	Operating Temperature	-40 ~ 60 °C with 11th Generation Intel® Core™ Processor i7-1185GRE/i3-1115GRE
	Non-operating Temperature	-20 ~ 60 °C with 11th Generation Intel® Core™ Processor i7-1185G7E/i5-1145G7E/i3-1115G4E
	Humidity	-40 ~ 85 °C
Mechanical	Mounting	5 ~ 95%
	System Cooling	DIN Rail/Wall Mount
	Dimensions (W x H x D)	Fanless
		70 x 150 x 120 mm/100 x 150 x 120 mm
OS	Windows	Windows 10
	Linux	Linux (Ubuntu)
Certification	EMC	EN50121-4, CE/FCC Class-B, CCC
	Safety	EN50121-4/UL/CB/CCC

**Dimensions**

Unit: mm




**I/O View**




**Dimensions**

Unit: mm



**I/O View**



**Ordering Information**

Part Number	CPU	SO-DIMM slots (DDR4)	LAN (RJ-45+SFP)	USB3.0 + USB2.0	COM	HDMI	MiniPCIe (extended board)	M.2	SSD	Msata/MiniPCIe (motherboard)	Operation temperature
ITA-260V1-00A1	I3-1115GRE	2	4	2+2	2	1	0	0	1	1	-40 ~ 60 °C
ITA-260V1-10A1	I7-1185GRE	2	4	2+2	2	1	0	0	1	1	-40 ~ 60 °C
ITA-260V1-01A1	I3-1115GRE	2	4+2	2+2	2	1	2	2	1	1	-40 ~ 60 °C
ITA-260V1-11A1	I7-1185GRE	2	4+2	2+2	2	1	2	2	1	1	-40 ~ 60 °C
ITA-260V1-00B1	I3-1115G4E	2	4	2+2	2	1	0	0	1	1	-20 ~ 60 °C
ITA-260V1-10B1	I7-1185G7E	2	4	2+2	2	1	0	0	1	1	-20 ~ 60 °C
ITA-260V1-20B1	I5-1145G7E	2	4	2+2	2	1	0	0	1	1	-20 ~ 60 °C

# Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



## AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 [www.autocont-ipc.cz](http://www.autocont-ipc.cz)



### PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



### POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



### AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



### PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



### NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



### INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



### MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



### SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



### PŘEJÍT DO E-SHOPU

[eshop.autocont-ipc.cz](http://eshop.autocont-ipc.cz)



### DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



### PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



### ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



### SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.