


# SOM-DB5830

## Development Board for COM Express® Type 6/10 Pin-Out Modules

NEW



CEFC

### Features


- PICMG COM R3.0 Type6 & Type10 pinout compatible
- COM ExpressR Basic/ Compact/ Mini module
- HDMI/DP, LVDS/eDP, VGA
- I/O Expansion:  
A2: PCIe Gen4 slot, USB3.2 Gen2  
A1: PCIe Gen3 slot, USB3.2 Gen2
- Visible Debug Utility: BIOS Port 80 and Power State

### Specifications

Form Factor		ATX
Compatible Models	Form Factor	Compatible to COM Express Basic, Compact, Mini Modules
	Pin-out Type	Type6/10 Pin-out Compatible
Display	VGA	1 (D-SUB 15P Female)
	LVDS/eDP	18/24-bit single or dual channel
	HDMI	1
	Display Port	2
Ethernet	Connector	Up to 2.5G (A1:1G, A2: 2.5G)
	Speed	10/100/1000/2500 Mbps
Expansion	PCI Express x16	1 Slot (Speed A1: Gen3, A2: Gen4)
	PCI Express x4	2 Slots (Speed A1: Gen3, A2: Gen4)
	LPC	Yes
I/O	SATA3.0	4 Ports
	USB3.2 Gen2	4 Ports (Type A)
	COM Port	2 Ports
	GPIO	8-bit
	SDIO	1 (Mux with GPIO)
	SPI Bus	Rev 1: Support SOP8 Socket Rev 2: Support SOP8, QFN8 Socket
	TPM	TPM2.0 (Infineon SLB9665) A1 only
	Port 80	1
	Fan	2 (1 smart fan from module side, 1 fixed-voltage fan)
	Audio	Line-in, Line-out, MIC, SPDIF (Realtek ALC888 HD Audio Codec)
Serial Bus	SMBus	Yes
	I <sup>2</sup> C Bus	Yes
	CAN Bus	Yes (Mux with SER1)
Power	Type	ATX: Vin, VSB; AT: Vin
	Supply Voltage	Vin: 4.5V ~ 20V; VSB: 4.75V ~ 5.25 V, RTC Battery: 2.0V ~ 3.3V
Environment	Operating Temperature	Standard: 0 ~ 60 °C (32 ~ 140 °F)
	Storage Temperature	-40 ~ 85 °C (-40 ~ 185 °F)
	Humidity	Operating: 40 °C @ 95% relative humidity, non-condensing Storage: 60 °C @ 95%relative humidity, non-condensing
	Vibration Resistance	3.5 Grms
Mechanical	Dimensions	304.8 mm x 244 mm (12" x 9.6")


# Block Diagram

## Block Diagram for A3




# Block Diagram

## Block Diagram for A2



# Block Diagram

Block Diagram for A1



## Ordering Information

Part Number	Version	COM Express Rev.	Type 6 Compatible	Type 10 Compatible	PCIe Bandwidth	eDP/LVDS	Height of COMe Connector	SOM-EA00	SOM-EA30 A2	Operating Temperature
SOM-DB5830-00A3	A3	Rev. 3.1	Yes	Yes	Gen 4	LVDS	5mm	SOM-EA00 A4	YES	0 ~ 60 °C
SOM-DB5830A-00A3	A3	Rev. 3.1	Yes	Yes	Gen 4	eDP	5mm	SOM-EA00 A4	YES	0 ~ 60 °C

Part Number	Version	COM Express Rev.	Type 6 Compatible	Type 10 Compatible	PCIe Bandwidth	eDP/LVDS	Height of COMe Connector	SOM-EA00	SOM-EA30 A2	Operating Temperature
SOM-DB5830-00A2	A2	Rev. 3.0	Yes	Yes	Gen 4	LVDS	5mm	SOM-EA00 A3	YES	0 ~ 60 °C
SOM-DB5830A-00A2	A2	Rev. 3.0	Yes	Yes	Gen 4	eDP	5mm	SOM-EA00 A3	YES	0 ~ 60 °C
SOM-DB5830X-00A2	A2	Rev. 3.0	Yes	Yes	Gen 4	LVDS	5mm	SOM-EA00 A3	YES	-40 ~ 85 °C

Part Number	Version	COM Express Rev.	Type 6 Compatible	Type 10 Compatible	PCIe Bandwidth	eDP/LVDS	Height of COMe Connector	SOM-EA00	SOM-EA30 A2	Operating Temperature
SOM-DB5830-00A1	A1	Rev. 3.0	Yes	N/A	Gen 3	LVDS	5mm	N/A	N/A	0 ~ 60 °C
SOM-DB5830A-00A1	A1	Rev. 3.0	Yes	N/A	Gen 3	eDP	5mm	N/A	N/A	0 ~ 60 °C

## Packing List

Part No.	Description	Quantity
SOM-EA10 A2	PCIe x4 – to 4 PCIe x1 Riser Card (Gen3)	1
SOM-EA00 A3	Type 6 to Type 10 Middle Board Rev.3.0	1
SOM-EA00 A4	Type 6 to Type 10 Middle Board Rev.3.1	1
SOM-EA30 A2	Type 6 Extension Card, Max.16G	1
1700008941	Serial ATA Cable 7P/7P 32cm	2
1701100300	Flat COM Port Cable	2

# Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



## AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 [obchod@autocont-ipc.cz](mailto:obchod@autocont-ipc.cz)

 +420 552 301 002

 [www.autocont-ipc.cz](http://www.autocont-ipc.cz)



### PRŮMYSLOVÉ POČÍTAČE

*fanless embedded PC, do racku, ...*



### POČÍTAČE S DISPLEJEM

*panelové PC, terminály, do vozidel, ...*



### AUTOMATIZACE A SBĚR DAT

*převodníky, karty, moduly, switche, ...*



### PERIFERIE A KOMPONENTY

*monitory, klávesnice, desky, skříně, ...*



### NOTEBOOKY A TABLETY

*odolné, windows, android, IP65, ...*



### INFORMAČNÍ KIOSKY

*interiérové, venkovní, ...*



### MEDICÍNSKÁ TECHNIKA

*počítače, tablety, LCD, klávesnice, ...*



### SOFTWAREVÁ ŘEŠENÍ

*pro výrobu, zaměstnance, kiosky, ...*



### PŘEJÍT DO E-SHOPU

[eshop.autocont-ipc.cz](http://eshop.autocont-ipc.cz)



### DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



### PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



### ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



### SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.