

PAX-127 Series

27" FHD Surgical Monitor



Features

- Widescreen 27" 1920x1080 resolution
- Optional 10-point touch function
- Gamma and DICOM calibrations
- Compliant with EN60601-1 MDR, EN60601-1-2 medical EMC and CCC certified



Introduction


PAX-127 is a versatile monitor with touch panel option. Suitable for applications in hospitals and clinical practice. With wipe clean surfaces and medical EMC compliance is ideal for equipment integrators.

Specifications

LCD	Resolution		1920 x 1080
	Aspect Ratio		16:9
	Pixel Pitch		0.3114 x 0.3114 mm
	Viewing Angle		178°/ 178°
	Contrast Ratio (Typ.)		1000:1
	Native Luminance (Typ.)		300cd/m² (Typical), 200±7 cd/m² (DICOM calibrated)
	Color Depth		8-bit 16.7M Colors
	Display Mode		IPS
	Response Time		14ms (Tr + Tf)
	Touchscreen	OPTIONAL	10-point PCAP
Backlight		LED	
Input	DP 1.2 Input	DP Jack x 1	DisplayPort 1.2, 1920 x 1080 @ 60Hz max.
	HDMI 1.4 Input	HDMI Jack x 1 (Type A)	Digital RGB: TMDS, 1920 x 1080 @ 60Hz max.
	DVI Input	DVI Jack x 1	Digital RGB: TMDS, 1920 x 1080 @ 60Hz max.
	Stero Mic		3.5mm Audio Jack x 1
	DC Power Input	4-pin DIN Jack x 1	DC 12V, 2.53A Max
Output	HDMI 1.4 Output	HDMI Jack x 1 (Type A)	Digital RGB: TMDS, 1920 x 1080 @60Hz max. loop out
	Stero Mic	3.5mm Audio Jack	Loop Out
	USB UP	USB-B	Touchscreen
	Internal Speakers		2x3W
	USB 2.0		2 ports
Environment	Temperature	Operational	0 ~ 40 °C
		Storage	-20 ~ 60 °C
	Humidity	Operational	Ta = 40 °C, 90% RH non-condensed
		Storage	5 ~ 90%
	Pressure	Operational	500 hPa to 1013 hPa
		Storage	500 hPa to 1013 hPa
Power	Rating		DC 12V, 2.53A
	Consumption (Typ.)		77.3W max.
Physical Characteristics	IP Ratings VESA Mount		Front IP65 / Top IPX1 100 x 100; 75 x 75 mm
	Dimension (W x D x H)		663.83 x 73.55 x 418.11 mm
	Weight		8.9kg max
Certifications	CE MDR (EN60601-1; EN60601-1-2), RoHS II, CCC		
Warranty	3 Years		
Accessories	Adapter		

Dimensions

Unit: mm



Ordering Information

SKU	Speciciation
PAX-127-C2A-LAG	AG Touch Panel
PAX-127-C2A-LAH	AG Glass

Power Cord List


Part No.	Description
1700019146	Power Cord CCC 3P 2.5A 250V 183cm(CCC)
170203183C	Power Cord EU 3P 2.5A 250V 183cm(CE)
1700001524	Power Cord UL 3P 10A 125V 183cm(UL)
170203180A	Power Cord BSI 3P 2.5A 250V 183cm(UK)
1700008921	Power Cord PSE 3P 7A 125V 183cm(Japan)
1700025113-11	Power Cord ISI 3P 2.5A 250V 180cm(India)
1700021375-01	Power Cord BSMI 3P 2.5A 125V 250cm (IEC60320-C5)(BSMI)
1700018553	Power Cord SAA 3P 2.5A 250V 183cm(Australian)

I/O Cover Design

For neat and hygienic cable management



I/O Ports



1. DC Input
2. DisplayPort
3. HDMI IN
4. HDMI OUT
5. DVI
6. Analogue Audio IN
7. Analogue Audio OUT
8. USB UP
9. USB 2.0 x 2

Recommended Mounting Solution

Model Name	ARES-2423R	
Part Number	ARES-2423R-A741L00	ARES-2423R-A741L01
Photo		
Max. Support Weight	6 - 12kg	
Max. Support Panel Size	≤ 27"	
VESA Information	75 x 75 mm 100x100 mm	

For more information, please click this link: <https://bit.ly/3T7dLMR>

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.