


AIMB-219

Mini-ITX Motherboard Intel® Core™ i3, N series and Atom® x7000 Series Processors (Alder Lake-N/ Amston Lake)



Features

- Intel® Core™ i3, N series and Atom® x7000 Series Processors
- Up to 16GB DDR4 3200MT/s with one SO-DIMM
- Triple independent display with 1 DP, 1 HDMI, 1 LVDS(or eDP)
- Abundant I/O expansion: 1 M.2 B-key & 1 M.2 E-key, 3 USB 3.2 Gen2x1, 5 USB 2.0, 1 USB Type-C and 6 COM
- Mini-ITX low profile motherboard, fanless design
- Supports Device-On and Embedded Software APIs

Software APIs:




Utilities:



Specifications

Processor System	CPU (10nm)	i3-N305	N200	N97	N50	x7835RE	x7433RE	x7213RE	x7211RE	
	Core Number	8	4	4	2	8	4	2	2	
	Base frequency (GHz)	1.8	1	2	1	1.3	1.5	2	1	
	TDP (W)	15	6	12	6	12	9	9	6	
	BIOS	AMI EFI 256Mb SPI								
Expansion Slot	M.2	1 x E-Key for wireless module (WiFi/BT), 1 x B-key for storage (SSD/LTE)								
	PCIe	1 PCIe x1 Gen3 (8GT/s)								
Memory	Technology	Single channel DDR4 3200 MT/s (non-ECC)								
	Max. Capacity	16 GB								
	Socket	1 x 260pin SO-DIMM								
Graphics	Controller	Intel® UHD Graphics								
	HDMI	1 x HDMI 2.1 TMDS, up to 4Kx2K @ 60 Hz (refer to Ordering Information)								
	DP	1 x DP 1.4a, up to 4096x2304 @ 60 Hz (via USB Type-C)								
	LVDS	1 (default, pin header, supports dual channel 18/24-bit, up to 1920 x 1200 @ 60 Hz)								
	eDP	1 (option, pin header, up to 4096 x 2304 @ 60 Hz)								
	Multi Displays	Triple displays								
	Network	Ethernet	10/100/1000/2500 Mbps							
Controller		RTL8111K (1GbE) or RTL8125BG (2.5GbE), refer to Ordering Information								
Connector		2 x RJ45								
Audio	Codec	Realtek ALC888S, High Definition Audio (HD), Line out, Mic-in								
	Amplifier	Yes, 6W								
SATA	Max data transfer rate	6.0 Gb/s								
	Channel	1 x SATAIII								
Rear I/O	DP (via USB Type-C)	1								
	HDMI	1								
	Ethernet	2								
	USB	2 x USB3.2 Gen2x1 + 1 x USB3.2 Gen2x1 Type-C								
	Audio	1 (Line-Out, Mic-In)								
Internal Connector	USB	5 x USB2.0 + 1 x USB3.2 Gen2x1 (Internal vertical Type-A)								
	LVDS/eDP	1 (eDP colay with LVDS)								
	Serial	6, COM1-COM2: Support RS-232 by default COM3: Support RS-232/422/485(BOM option), auto flow control by BIOS COM4: Support RS-232 by default; CClalk by BOM option COM5: Support RS-232 by default; TTL by BOM option COM6: Support RS-232 by default; Ring-in 5V/12V select by jumper								
		SATA	1 x SATAIII 6.0 Gb/s							
		M.2	1 x B-key (dimension: 2242/2280/3042) 1 x E-key (dimension: 2230)							
		GPIO	8-bit							
		Watchdog Timer	Output	System reset						
	Interval		Programmable 1 ~ 255 (second or minute)							
Power Requirements	Input voltage	12V DC-in								
	Connector	DC Jack, Internal 4-pin ATX								
	Power consumption	Configuration	Intel Core i3-N305, 1pcs 16 GB DDR4 3200MT/s SO-DIMM							
		Max.	39.7 W							
Environment	Typical	26.4 W								
	Temperature	Operating: 0 ~ 60 °C (32 ~ 140 °F) or -20 ~ 70 °C (-4 ~ 158 °F) for Z SKU								
Physical Characteristics	Storage	Non-Operating: -40 ~ 85 °C (-40 ~ 185 °F)								
	Dimensions	170 mm x 170 mm (6.69" x 6.69")								

Block Diagram



Ordering Information

P/N	CPU	HDMI 2.1 TMDS	HDMI FHD	LVDS/eDP	USB Type-C	GbE	COM	SATAIII	USB3.2	USB2.0	M.2 B key	M.2 E key	PCIex1	TPM	AMP	Thermal Solution	Operating Temp.
AIMB-219NC3F-LDA1	i3-N305	1	0	1/(1)	1	2*	6	1	3	5	1	1	1	1	1	Passive	0 ~ 60 °C
AIMB-219N2F-LDA1	N200	0	1	1/(1)	(1)	2	4/(2)	1	3	5	1	1	1	1	(1)	Passive	0 ~ 60 °C
AIMB-219N9F-LDA1	N97	0	1	1/(1)	1	2	4/(2)	1	3	5	1	1	1	1	(1)	Passive	0 ~ 60 °C
AIMB-219N5L-LDA1	N50	0	1	0	0	1/(1)	2/(4)	1	3	2/(3)	1	1	1	(1)	(1)	Passive	0 ~ 60 °C
AIMB-219M8F-LDA1	x7835RE	1	0	1/(1)	1	2*	6	1	3	5	1	1	1	1	1	Passive	0 ~ 60 °C
AIMB-219M4F-LDA1	x7213RE	0	1	1/(1)	(1)	2	4/(2)	1	3	5	1	1	1	1	(1)	Passive	0 ~ 60 °C
AIMB-219M6F-LDA1	x7433RE	0	1	1/(1)	1	2	4/(2)	1	3	5	1	1	1	1	(1)	Passive	0 ~ 60 °C
AIMB-219Z6F-LDA1	x7433RE	0	1	1/(1)	1	2	4/(2)	1	3	5	1	1	1	1	(1)	Passive	-20 ~ 70 °C
AIMB-219M2L-LDA1	x7211RE	0	1	0	0	1/(1)	2/(4)	1	3	2/(3)	1	1	1	(1)	(1)	Passive	0 ~ 60 °C

*() Supports by BOM options

* AIMB-219NC3F-LDA1 and AIMB-219M8F-LDA1: default 2.5 GbE x2; the other SKU support 2.5GbE by option.

Packing List

Part Number	Description	Quantity
AIMB-219 Board	AIMB-219 motherboard	1
1700003194-21	SATA HDD cable	1
1700034404-01	1-to-1 serial port cable, 50cm	1
1960115632T001	I/O port bracket	1
2046021900	Startup manual for AIMB-219	1
1970005854T001	Fanless heatsink for CPU i3-N305 or N97	1
1960064228T011	Fanless heatsink for CPU N200 or N50	1
19350304A0	M.2 Screw, M3x4L R/S D=5.3 H=2 (2+)	2
1910003418-01	M.2 Post, F=M3x4L M=M3x3L B=5 H=5.2	1
1700018785-01	SATA power cable	1

I/O View



Optional Chassis

Part Number	Description
AIMB-B2000-00YE	Mini-ITX chassis with optional DC Adaptor

Optional Accessories

Part Number	Description
1700034405-01	1-to-1 USB cable, 50cm
96PSA-A120W12V1-3	Adapter AC100-240V 120W 12V

Embedded OS/API

OS	Part No.	Description
Ubuntu	20706U22DS0039	img UbuntuD AIMB-219 64b 22.04 ENU
Windows 10	20706WX1ES0083	img W10 21EL AIMB-219 64b 21H2 ENU
Windows 10	20706WX1HS0083	img W10 21HL AIMB-219 64b 21H2 ENU
Windows 10	20706WX1VS0083	img W10 21VL AIMB-219 64b 21H2 ENU

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.