

USC-513 Series

13.3" Integrated POS Terminal USC-513K with Intel® Alder Lake N305/N97



Features

- Supports DeviceOn/iService software for remote device management
- 13.3" FHD LCD (LED backlight) with PCAP touch
- Ultra-thin design with 14 mm narrow bezel
- Multi-function base integrated thermal printer and barcode scanner
- Rich peripherals for diverse applications
- Compact design with small footprint for saving counter space
- G-sensor embedded in main screen to support multiple orientations
- Support Win 11 LTSC/Linux OS

Introduction

The USC-513 is a cost-effective integrated point-of-sale (POS) system tailored for diverse retail and hospitality applications. With its sleek modern design, the USC-513 integrates a printer and barcode scanner, streamlining payments and receipt printing in a compact terminal.

Its compact size optimizes space utilization, providing retailers with more space for product displays and promotions. The USC-513 is ideal for retail environments, such as restaurants, convenience stores, cafes, and shopping malls, especially for areas with limited counter space for POS system installation.

Specifications

Model	USC-513K	
System	CPU	Intel® Alder Lake-N N97/Core I3-N305
	Technology	DDR5-4800, 1 x 262-pin SO-DIMM
Memory	Max. capacity	16GB
Storage	1x M.2 M-key 2242 SATA	
LCD Panel	Display Size	13.3" widescreen (16:9) FHD LCD (LED backlight)
	Resolution	1920 x 1080
	Viewing Angle	Horizontal: ±80°, Vertical: ±80°
	LCD Luminance	300 cd/m²
	Contrast Ratio	1500:1
Touch Screen	Main Display	Projected Capacitive Touch Panel (PCAP, flat glass)
	2nd Display	Non-touch, flat glass (PCAP optional)
I/O Port	LAN	1 x RJ-45 2.5G LAN Ethernet
	USB	2 x USB 3.0, 4 x USB 2.0
	Serial Port	1 x RJ45 (10PIN, COM1, support RS232); 2 x DB9 (COM2 support RS232 /RS485/RS422; COM3 support RS232, no power, 5V/12V by request)
	Cash Drawer	1 x Cash drawer port, 12V
Others	Speaker	2 x 2 W speakers
	Flipable Main Display	Embedded G-sensor
	Adapter	24V _{DC} /180W
Peripherals	Wi-Fi/Bluetooth	1 x M.2 2230 E-Key for Wi-Fi & BT combo (optional)
	RFID	Supports ISO/IEC 14443A/MIFARE Reader, FeliCa Reader, ISO/IEC 14443B Reader (Optional)
	Barcode Scanner	NLS-EM27-01, embedded 1D/2D scanner, supports QR code (optional)
	Printer	PM381, embedded 80 mm thermal printer with auto-cutter, 170 mm/s max
	2nd Display	13.3" FHD LCD with or without touch screen (optional)
	MSR	Available ISO TK1, 2 & 3 (optional)


Specifications (Cont.)

Mechanical Specifications	Color	White and black
	Dimensions (W x D x H)	171.5 x 170 x 305 mm (dual display) 171.5 x 170 x 246 mm (single display) 440 x 400 x 430 mm (package)
	Weight	6.4/4 kg (dual or single display)
Environmental	Operating Temperature	0 ~ 40°C (32 ~ 104°F)
	Humidity	max. 95% @ 40°C (104°F) (non-condensing)
	Shock	10G peak acceleration (11 ms duration)
	Vibration	5 ~ 500 Hz 0.5 Grms, random
Certifications		CE, CCC, FCC, CB, BSMI
DeviceOn/iService Remote Device Management Software	Operating System	Windows 11, Linux
	Common Controls (Reboot, Shutdown)	✓
	Remote Desktop	✓ (VNC)
	Device-Specific Controls (Audio, Backlight)	✓
	Connection Status	✓
	Hardware Status	✓
	Batch Operation Support	✓
	OTA Storage Management	Local blob
	OTA Software Updates	✓
	Software Watchlist	✓
	Software Start/Stop	✓
	Kiosk Mode	✓
	Peripherals Watchlist	✓

Note: DeviceOn/iService software must be downloaded from the Advantech website at <https://www.advantech.com/search/?q=DeviceOn%2FiService&st=support&sst=Utility>

Dimensions

Unit: mm



Ordering Information


Part Number	Description
USC-513KP-WI323	13.3", dual FHD, PCAP & Glass, N305, 8GB RAM, 128GB M.2, Printer & Scanner & MSR, Adapter, no G-S, White&Black
USC-513KP-WN923	13.3", dual FHD, PCAP & Glass, N97, 8GB RAM, 128GB M.2, Printer & Scanner & MSR, Adapter, no G-S, White&Black
USC-513KP-WI310	13.3", Single FHD, PCAP, N305, 8GB RAM, 128GB M.2, Printer only, Adapter, G-S, Lite White&Black
USC-513KP-WN910	13.3", Single FHD, PCAP, N97, 8GB RAM, 128GB M.2, Printer only, Adapter, G-S, Lite White&Black

Installation Accessories

Part Number	Description
96CB-POWER-B-1.8MB	Power cable 3P, CCC, 10A, 250V, 180 cm (China)
1700001524 / 1700001524-01	Power cable 3P, UL, 10A, 125V, 180 cm (US, TW)
170203183C / 170203183C-01	Power cable 3P, 10A, 250V, 183 cm (EU)
1700018553 / 1700018553-01	Power cable 3P, SAA, 2.5A, 250V, 183 cm (Australia)
1700025113-11	Power cable, ISI, 3P, 2.5A, 250V, 180 cm (India)
1700018409	Power cable, KCC, 2P, 2.5A, 250V, 183 cm (Korea, Russia)
170203180A / 170203180A-01	Power cable, BSI, 3P, 2.5A, 250V, 183 cm (UK)
1700008921 / 1700008921-11	Power cable, PSE, 3P, 7A, 125V, 180 cm (Japan)
EWM-W159M201E	new M.2 2230 WiFi5+BT5.0 module
1751000522-01	Metal Ant.D.B 2.4+5G WIFI Main MHF4/113 BLK L265
1751000523-01	Metal Ant.D.B 2.4+5G WIFI Aux MHF4/113 WHT L300

Outlook


Dual Display



Single Display



I/O Layout



Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.