

PCI-1716/L/H

16-ch, 16-bit, 1 MS/s or 250 kS/s Multifunction PCI Card



FCC CE 

Features

- 16 single-ended or 8 differential or a combination of analog inputs
- 16-bit A/D converter, with up to 1 MS/s or 500 KS/s sampling rate
- FIFO memory (8,192 samples)
- Auto-calibration
- 2 analog output channels (PCI-1716/PCI-1716H only)
- 16-ch digital input and 16-ch digital output
- BoardID switch

Specifications

Analog Input

- **Channels** 16 single-ended, 8 differential, or combination
- **Resolution** 16 bits
- **Sample Rate** 1 MS/s max. for PCI-1716H
250 kS/s max. for PCI-1716/L
shared by all enabled channels
- **Convert Clock Source** Internal or external
- **Overvoltage Protection** ± 15 V
- **Input Impedance** 100 M Ω
- **Integral Non-Linearity (INL)** ± 1 LSB max.
- **Differential Non-Linearity (DNL)** ± 1 LSB max.
- **Input Range & Absolute Accuracy***

Unipolar (V)		0 ~ 10	0 ~ 5	0 ~ 2.5	0 ~ 1.25
Bipolar (V)	± 10	± 5	± 2.5	± 1.25	± 0.625
Absolute Accuracy (% of FSR)	0.01	0.025	0.025	0.04	0.075

Analog Output (PCI-1716/PCI-1716H only)

- **Channels** 2
- **Resolution** 16 bits
- **Update Rate** 1 MS/s max. per channel
- **Update Clock Source** Internal or external
- **Output Range**
Internal Reference ± 10 V, ± 5 V, 0 ~ 10 V, or 0 ~ 5 V
External Reference $\pm x$ V or 0 ~ $+x$ V @ $+x$ V reference
($-10 \leq x \leq +10$)
- **Absolute Accuracy** $\pm 0.01\%$ of full-scale range max.
- **Slew Rate** 20 V/ μ s
- **Driving Capability** ± 20 mA max.
- **Output Impedance** 0.1 Ω max.

Digital Input

- **Channels** 16
- **Compatibility** 5 V/TTL
- **Input Voltage** Logic 0: 0.8 V max.
Logic 1: 2.0 V min.

Digital Output

- **Channels** 16
- **Compatibility** 5 V/TTL
- **Output Voltage** Logic 0: 0.4 V max. @ 2 mA sink
Logic 1: 4.0 V min. @ 2 mA source/5.2 V max.

Counter

- **Channels** 1
- **Resolution** 32 bits
- **Compatibility** 5 V/TTL
- **Function** Event counting, frequency measurement, one-shot, and timer/pulse
- **Input Frequency** 10 MHz max.

General

- **I/O Connector** 1 x 68-pin SCSI female connector
- **Dimensions (L x H)** 175 x 100 mm (6.9" x 3.9")
- **Power Consumption** +5 V: 500 mA typ., 800 mA max.
+12 V: 150 mA typ., 400 mA max.
- **Operating Temperature** 0 ~ 60°C (32 ~ 140°F)
- **Storage Temperature** -20 ~ 70°C (-4 ~ 158°F)
- **Operating Humidity** 10 ~ 90% RH non-condensing
- **Storage Humidity** 5 ~ 95% RH non-condensing

Ordering Information

- **PCI-1716-B1** 16-ch, 16-bit, 250 kS/s Multifunction PCI Card
- **PCI-1716L-B1** 16-ch, 16-bit, 250 kS/s Multifunction PCI Card w/o AO
- **PCI-1716H-AE** 16-ch, 16-bit, 1 MS/s Multifunction PCI Card

Accessories

- **PCLD-8710-AE** DIN-rail Wiring Board w/ CJC
- **PCL-10168-1E** 68-pin SCSI Shielded Cable, 1 m
- **PCL-10168-2E** 68-pin SCSI Shielded Cable, 2 m
- **ADAM-3968-AE** 68-pin DIN-rail SCSI Wiring Board

* For detail information, please refer to user manual.

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.