

R19L100-SPM169-P, 19-inch Stainless P-Series Display

Stainless IP69K with Waterproof Conduit Solutions

Winmate provides 19-inch IP69K Stainless Steel Display with a waterproof conduit pipe for added cable protection. The IP69K series is built to withstand extensive wash downs with corrosion resistance against cleaning agents, especially against close-range high-pressure, high temperature wash downs. The level of protection allows for easy cleaning and sterilization using water with temperatures of up to 80°C and pressure of up to 30 Bar. A custom-built waterproof conduit pipe was also provided for the customer with a cover plate, allowing for an additional layer of protection for the cables.



** Yoke mount Stand kit is an option. accessory.*

Highlights

- Projected capacitive multi-touch screen
- Waterproof Conduit pipe for extra protection
- True flat, easy-to-clean front surface
- IP69K water and dust proof, allows high pressure and high temperature cleaning
- SUS 316/ AISI 316 stainless steel for food and chemical industries
- Multiple mounting solutions for different scenario applications
- Supports VESA mount, Panel mount and optional Yoke mount stand

R19L100-SPM169-P, 19-inch Stainless P-Series Display

Stainless IP69K with Waterproof Conduit Solutions

Display Specification

Size	19"
Resolution	1280 x 1024
Contrast Ratio	1000:1
Brightness	250 nits
Viewing Angle	-85~85 (H); -80~80(V)
Max Colors	16.7M
Touch	Projected Capacitive Multi-Touch (P-CAP) Anti-glare coating (Optional)

Interface

USB Ports	1 x USB for Touch
HDMI	1 x HDMI input
VGA	1 x VGA

Keyboard and Input

Physical Buttons	5 Keys: -, +, Power, Esc, Enter
LED Indicators	Power & Stand by
Touch	P-Cap

Standards and Certification

EMC	CE, FCC
-----	---------

Power Management

Power Input	12V DC input with AC to DC Adapter Optional 9~36V DC input with 3 pin phoenix connector
Power Consumption	23W (typ.)(Max.backlight and high CPU load)
AC Adapter	100~240V AC to 12V DC Adapter

Mechanical Specifications

Dimensions	445 x 370 x 56mm
Cutout	427 x 352mm
Cooling System	Fanless design
Housing	SUS 316/ AISI 316 stainless steel
Mounting	VESA Mount (100x100mm), Panel mount, optional Yoke mount stan

Environment

Operating Temperature	0 °C to 45 °C
Storage Temperature	-10 °C to 60 °C
Operating Humidity	10% to 95% (non condensing)
IP Rating	IP69K

Accessories


Standard

1 x Waterproof Conduit 1.5 m
2 x Elbow for Connect the Conduit
1 x AC to DC Power Adapter with Power Cord
1 x External USB Cable for Touchscreen Control
1 x External RJ45 Cable
D-sub to RJ45 Adaptor for VGA Port
Open wire cable for phoenix connector (Default for 9~36V DC input SKU)

Optional

Yoke Mount Stand Kit

Drawing




* Yoke mount Stand kit is an option. accessory.

R19L100-SPM169-P, 19-inch Stainless P-Series Display


Stainless IP69K with Waterproof Conduit Solutions

Accessories


Waterproof Conduit 1.5m



AC to DC power adapter




Open wire cable for phoenix connector (Default for 9~36V DC input sku)



Pin No.	Symbols	Color	Pin No.	Symbols	Color
Open wire 5mm		Red	Open wire 5mm		Red
Open wire 5mm		Black	Open wire 5mm		Black
Open wire 5mm		Green	Open wire 5mm		Green

Yoke mount Stand kit (Optional)




D-sub to RJ45 Adaptor



Elbow for connect the conduit




RJ45 Cable




Pin No.	Symbols	Color	Pin No.	Symbols	Color	
CN1-1		White/Orange	CN2-1		White/Orange	Twisted pairs
CN1-2		Orange	CN2-2		Orange	
CN1-3		White/Green	CN2-3		White/Orange	Twisted pairs
CN1-4		Blue	CN2-4		Blue	
CN1-5		White/Blue	CN2-5		White/Blue	Twisted pairs
CN1-6		Green	CN2-6		Green	
CN1-7		White/Brown	CN2-7		White/Brown	Twisted pairs
CN1-8		Brown	CN2-8		Brown	

HDMI Cable



Plug	Conn.	Plug	Conn.
1	Brown	10	Blue
2	Drain	11	Drain
3	White	12	White
4	Red	13	Black
5	Drain	14	Red
6	White	15	Orange
7	Green	16	Yellow
8	Drain	17	Drain
9	White	18	Purple
		19	White
		Shell	Drain+Braid
			Shell

USB Cable



Pin No.	Symbols	Color	Pin No.	Symbols	Color
CN1-1	USB-VBUS	Red	CN2-1	USB-VBUS	Red
CN1-2	USB-D-	White	CN2-2	USB-D-	White
CN1-3	USB-D+	Green	CN2-3	USB-D+	Green
CN1-4	USB-GND	Black	CN2-4	USB-GND	Black
CN1-5	Braid		CN2-5	Braid	

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.