



15" Panel PC (Intel® 3rd Generation Core™ i7 / i5)


Mechanical design




- | | |
|-------------------------------|-------------------|
| 1. Brightness Adjustment Knob | 7. RJ-45 |
| 2. OSD Membrane | 8. VGA Out |
| 3. RS-232 Conn.(Optional) | 9. RS-232/422/485 |
| 4. Audio Jack | 10. RS-232 Conn. |
| 5. DVI (Optional) | 11. PS/2 |
| 6. USB | 12. 12V DC-IN |

Fully Integrated I/O


Dimensions



BOTTOM VIEW



SIDE VIEW



BACK VIEW

- * Measurements shown in mm
 * Tolerance of all dimensions is shown as follow 0~30 mm ± 0.1 mm,
 30~50 mm ± 0.15 mm, 50~120 mm ± 0.2 mm, above 120 mm ± 0.25 mm
 * Note: this is a simplified drawing and some components are not marked in detail.
 Please contact our sales representative if you need further product information.

System Specifications :

- CPU : Intel® 3rd Generation Core™i7-3520M 2.9GHz, turo to 3.6GHz
Intel® 3rd Generation Core™i5-3230M 2.6GHz, turo to 3.2GHz
- System Chipset : Intel HM76 Chipset
- System Memory : 2 x DDR3L 1333/1600MHz SO-DIMM, max. 16GB
- Audio : Realtek ALC886 HD Audio Codec
- Network : Dual Broadcom BCM57780 PCIe GbE LAN Controller
- IDE/SATA : 1 x SATA III, 1 x SATA II

Input / Output :

- Serial Ports : 2 x RS232, *1 x RS232/422/485
- USB Ports : 4 x USB 3.0
- Keyboard / Mouse : 2 x PS/2
- Ethernet : 2 x RJ 45-10/100/1000 Mbps
- VGA : 1 x VGA (female)
- Audio : Line-Out, Line-In, Mic in

- Default setting: RS232

Expansion Slot :

- 2 x Mini PCIe (1 for WiFi, 1 for WWAN Module), 1xPCIe x16 , 1xPCIe x 4
- * A customized housing is needed if you would like to have the PCIe expansion.

* A customized housing is needed if you would like to have the PCIe expansion.

Power Management :

- Power Input : 12V DC IN (Lockable Power Jack)
- Power Consumption : 87W (typ.)(Max.backlight & high CPU load)

Accessories :

- External Adapter : 110~240V Ac-in Power Adapter

Display Specifications :

- Size/Type : 15" T FT
- Resolutions : 1024 x 768
- Contrast Ratio : 2000 : 1
- Brightness : 300 nits (Optional 400 nits)
- Viewing Angle : -88~88(H);-88~88(V)
- Max. Colors : 16.2M

Environment :

- Operating Temperature : 0°C to 50°C
- Operating Humidity : 30% to 90% (non condensing)

OS BSP / Driver Support :

- Support Windows 10 IoT Enterprise / Windows 8 Embedded / Windows 7 Embedded

Order Options :

- | | |
|------------|---|
| Mechanical | : Open Frame |
| Touch | : 5 Wire Resistive (Optional)
AR Glass(Optional) |

- | | |
|-----------|---|
| Storage : | 2.5"HDD/2.5" SSD/ mSATA SSD |
| RAM : | DDR3L 1333/1600MHz SO-DIMM,
max. 16GB |
| OS : | Windows 10 IoT Enterprise
Windows 8 Embedded
Windows 7 Embedded |

(A customized housing is needed if you have demands of SAW/IR/SC touch)

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.