

IE32SB3-101

Intel® Celeron® N6211 M Series Box PC



KEY FEATURES

- Intel® Celeron® Elkhart Lake N6211 Processor
- 1 x DDR4 SO-DIMM 3200 MHz, max. 16GB
- 2 x Gigabit Ethernet
- Supports 2 x USB 3.2 Gen 2x1, Max. 3 x COM
- Elegant and slim mechanical design
- Fanless cooling system
- Optional Capture Card for HDMI input or CVBS input



SPECIFICATIONS


System Specification			
WLAN	Support (Optional)	BT	Support (Optional)
Processor	Intel® Celeron® N6211 (up to 3.0GHz) Intel® Celeron® N6210 (up to 2.6GHz) (Optional)	Memory	1 x SO-DIMM, DDR4 3200 MHz, 4GB 8GB (Optional) 16GB (Optional)
Storage	1 x M.2 2242 B-key SSD 128GB 256GB (Optional) 512GB (Optional)	Ethernet controller	2 x Intel® Ethernet Controller
Security	TPM 2.0	Operating System	Windows 11 IoT Enterprise (64 bit) (Optional) Windows 11 Pro 64 bit (Optional) Windows 10 IoT Enterprise (64 bit) (Optional) Linux Ubuntu 22.04 (Optional)
Mechanical			
Dimension	205 x 110 x 55 mm	Weight	1.1 kg
Mounting	Desk Mount	Enclosure	Metal Housing
Cooling System	Fanless design		
Environment			
Operating Humidity	10% to 90% RH, Non-Condensing	Operating Temperature	0°C to 55°C
Storage Temperature	-10°C to 60°C		
Certification			
Certification	CE, FCC		
IO Ports			
Power Input	1 x 12V DC, 2.5φ DC jack	USB Port	2 x USB3.2 Gen2x1 (Type-A)
Serial Port	1 x RS232/422/485 (Default RS232) 1~2 x RS232 (Optional)	Video	1 x HDMI 2.0 (Optional)
Expansion Port	1 x M.2 2242 Key B slot for SSD 1 x M.2 2230 Key E slot for Wi-Fi 1 x Capture Card for HDMI input or CVBS input (Optional)	LAN	2 x Giga LAN RJ45 Connector
Control			
Button	1 x Power Button		
Accessory			

Accessory	1 x 100~240V AC to DC Adapter 1 x Power Cord 1 x Quick Start Guide 6 x M4*8 desk mount screws
------------------	--


Power

Power Rating	12V DC in
---------------------	-----------

DIMENSIONS UNIT:MM




Front side I/O



1 Power Switch


Rear side I/O




2 LAN
3 HDMI
4 USB Type-A
5 COM
6 Power Input

Ordering Information

1. Customer can optional add max. 2 ports COM
 2. Customer can optional add HDMI Input
 3. Customer can optional add CVBS Input
- *Note: 2 and 3 are either one optional I/O ports.



2 LAN
3 HDMI
4 USB Type-A
5 COM
6 Power Input
7 COM (Optional)
8 HDMI Input (Optional)



2 LAN
3 HDMI
4 USB Type-A
5 COM
6 Power Input
7 COM (Optional)
8 CVBS Input (Optional)

NOTE

- 1.This is a simplified drawing and some components are not marked in detail.
- 2.Please contact our sales representative if you need further product information.
- 3.All specifications are subject to change without prior notice.
- 4.The product shown in this datasheet is a standard model.For diagrams that contain customized or optional I/ O, please contact the Winmate Sales Team for more information.

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.