

IK32

Intel® Core™ i5-7200U Single Computer Board



KEY FEATURES

- 3.5" Form Factor (146mm x 102mm), single computer board
- Intel® Core™ i5-7200U Processor
- Intel® SoC Integrated
- One DDR4-2133 SO-DIMM RAM
- Integrated Dual Gigabit Ethernet
- 2 x SATA III, 5 x COM, 2 x USB 3.0, 4 x USB 2.0
- 1 x M.2 2242 Key B Slot (for SATA III SSD)
- 1 x M.2 2230 Key E Slot (for PCIe + USB 2.0 Wireless Module)
- 1 x HDMI

INTRODUCTION

Winmate x86 Embedded Board Series combines compact design with powerful performance, featuring multiple advanced processor options. Designed with industrial-grade components, advanced and versatile customization capabilities, this Embedded Board ensures reliable operation in harsh environments with a wide power input range of 9-36V and extended temperature tolerance (-40 to +85°C). Ideal for space-constrained industrial applications, they deliver seamless integration and optimized performance.

SPECIFICATIONS

System Specification

Processor	Intel Core i5-7300U 2.6GHz (up to 3.5GHz)	Memory	1 x SO-DIMM, DDR4 2133 MHz, 4GB 8GB (Optional) 16GB (Optional)
Storage	1 x M.2 2242 SSD 128GB 256GB (Optional) 512GB (Optional)	Ethernet controller	2 x Intel® Ethernet Controller
Security	TPM 2.0	Operating System	Windows 10 IoT Enterprise (64 bit) (Optional) Linux Ubuntu 20.04 (Optional)
WLAN	Support (Optional)	BT	Support (Optional)

IO Ports

Power Input	1 x 12V DC, 2.5φ DC jack	USB Port	2 x USB3.2 Gen1x1 (Type-A)
Serial Port	1 x RS232/422/485 (Default RS232)	Video	1 x HDMI 1.4 (Optional)
Expansion Port	1 x M.2 2242 B-key Slot (for SATA III SSD) 1 x M.2 2230 E-Key Slot (for Wi-Fi module)	LAN	2 x Giga LAN RJ45 Connector

Internal IO Ports

Power input	1 x 2pin(1x2) for 12V DC in 1 x 4pin(1x4) for 12V DC in	Power output	1 x 2pin(1x2) blue wafer for 3.3V DC out 1 x 2pin(1x2) red wafer for 5V DC out 1 x 2pin(1x2) yellow wafer for 12V DC out
USB	2 x 8pin(2x4) for 4 x USB 2.0	Serial port	4 x 10pin(2x5) for RS232
Display	1 x 40pin DF13 connector for LVDS	Backlight	1 x 7pin(1x7) for panel backlight

	1 x 30pin DF13 connector for eDP (Optional) 1 x 10pin(2x5) for VGA (Optional)		
SATA	2 x SATA III 1 x 8pin(2x4) for SATA power	DIDO	1 x 14pin(2x7) for Digital input/output
VR	1 x 3pin(1x3) for Digital panel backlight brightness control 1 x 3pin(1x3) VR/Software brightness switch jumper 1 x 3pin(1x3) PWM/DC brightness switch jumper 1 x 3pin(1x3) 3.3V/5V PWM Level switch jumper	Fan	1 x 3pin(1x3) for CPU Fan
OSD	1 x 10pin(2x5) for OSD control	Speaker	2 x 2pin(1x2) for Speaker
Backup battery	1 x 2pin(1x2) for RTC battery	Audio	1 x 12pin(2x6) for Line in/Line out/ Mic in
BIOS debug	1 x 10pin(2x5) for LPC debug		

Certification

Certification	CE, FCC
----------------------	---------

Mechanical

Dimension	146 x 102 mm
------------------	--------------

Environment

Operating Humidity	10% to 95% RH, Non-Condensing	Operating Temperature	0°C to 60°C
Storage Temperature	-40°C to 70°C		


Accessory

Accessory	1 x Installation Guide	Optional Accessory	1 x SATA cable (94H007Z070K0) (Optional) 1 x SATA Power cable (94HE08Z150E0) (Optional) 1 x COM cable (94G309E100E1) (Optional) 1 x 2-Port USB 2.0 Type A cable (94E808E080K0) (Optional) 1 x 12V 120W Adapter (922D120W12V5) (Optional) 1 x Power cord (Varies by country) (Optional) 1 x CPU Heatspreader (98K000A000N3) (Optional) 1 x Membrane (98K000A000N1) (Optional) 2 x Speaker (612620000007) (Optional)
------------------	------------------------	---------------------------	--

Power

Power Rating	12V DC
---------------------	--------

DIMENSIONS UNIT:MM



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. Please contact our sales representative if you need further product information.
3. All specifications are subject to change without prior notice.
4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.

Tento produkt můžete zakoupit u společnosti AutoCont IPC a.s.



AutoCont IPC a.s.

Váš dodavatel průmyslových počítačů, komponent a speciálních průmyslových IT systémů.

 Uhlířská 1064/3, 710 00 Ostrava, Česká republika

 obchod@autocont-ipc.cz

 +420 552 301 002

 www.autocont-ipc.cz



PRŮMYSLOVÉ POČÍTAČE

fanless embedded PC, do racku, ...



POČÍTAČE S DISPLEJEM

panelové PC, terminály, do vozidel, ...



AUTOMATIZACE A SBĚR DAT

převodníky, karty, moduly, switche, ...



PERIFERIE A KOMPONENTY

monitory, klávesnice, desky, skříně, ...



NOTEBOOKY A TABLETY

odolné, windows, android, IP65, ...



INFORMAČNÍ KIOSKY

interiérové, venkovní, ...



MEDICÍNSKÁ TECHNIKA

počítače, tablety, LCD, klávesnice, ...



SOFTWAREVÁ ŘEŠENÍ

pro výrobu, zaměstnance, kiosky, ...



PŘEJÍT DO E-SHOPU

eshop.autocont-ipc.cz



DOPRAVA ZDARMA

Doprava zdarma v ČR a SR při objednávce nad 10 000 Kč bez DPH nebo nad 400 EUR.



PRODLOUŽENÁ ZÁRUKA

Záruka 2 roky na vyráběné počítače s možností jejího prodloužení až na 5 let.



ODMĚNA ZA VĚRNOST

Pravidelní zákazníci u nás nakupují za nižší ceny. Výše slevy se odvíjí od realizovaného obrátu.



SERVIS ON-SITE A IN-TIME

K projektovým dodávkám nabízíme rozšířenou podporu a servis s garancí výměny zařízení do 48 hodin.